

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NM-03563

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Page 3F

9. API WELL NO.

30-045-34105

10. FIELD AND POOL, OR WILDCAT

Basin Dakota/Blanco Mesa Verde

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec.20 T30N R10W, NMPM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐

2. NAME OF OPERATOR

ConocoPhillips

3. ADDRESS AND TELEPHONE NO

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Unit E (SWNW) 1727 FNL & 1035' FWL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO DATE ISSUED

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

15. DATE SPUNDED 3/27/07

16. DATE T.D. REACHED 4/16/07

17. DATE COMPL. (Ready to prod.) 6/10/07

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* GL 6289' KB 6305'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 7445'

21. PLUG, BACK T.D., MD & TVD 7415'

22. IF MULTIPLE COMPL., HOW MANY* 2

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesa Verde 4912' - 5315'

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Cement bond Log w/Gamma Ray Casing Collars

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	231'	13 1/2"	surface; 68sx (109 cf)	2 bbls
7" J-55	20# & 23#	4768'	8 3/4"	surface; 785sx (1592 cf)	80 bbls
4 1/2" J-55	11.6# 10.5	7436'	6 1/4"	TOC 4630' ; 217sx (428 cf)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	7269'	

31. PERFORATION RECORD (Interval, size and number)

@1SPF
4912' - 5315'
Total Holes = 30

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

4912' - 5315' Bullhead 10 bbls 15% HCL Acid. Pumped 59346 gal
Slickwater w/130000# 20/40 Brady Sand.

RCVD JUN 28 07
OIL CONS DIV.
DIST. 3

33. DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump)

SI W/O Facilities

Flowing

WELL STATUS (Producing or shut-in)

SI

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO
6/8/07	1	1/2"			28.71 mcf		
FLOW. TUBING PRESS	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)	
110#	SI 300#		0	689 mcf/d			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a MVD/K well being DHC per order #2509 AZ.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Regulatory Technician TITLE Regulatory Technician

DATE

6/25/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

JUN 27 2007

FARMINGTON FIELD OFFICE

Ojo Alamo	1506'	1569'
Kirtland	1569'	2405'
Fruitland	2405'	2787'
Pictured Cliffs	2787'	2932'
Lewis	2932'	3527'
Huerfanito Bentonite	3527'	3791'
Chacra	3791'	4304'
Mesa Verde	4304'	4595'
Menefee	4595'	5121'
Point Lookout	5121'	5515'
Mancos	5515'	6342'
Gallup	6342'	7079'
La Ventana	XXXX	XXXX
Greenhorn	7079'	7131'
Graneros	7131'	7185'
Dakota	7185'	

White, cr-gr ss.
 Gry sh interbedded w/tight, gry, fine-gr ss.
 Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.
 Bn-Gry, fine grn, tight ss.
 Shale w/siltstone stringers
 White, waxy chalky bentonite
 Gry fn grn silty, glauconitic sd stone w/drak gry shale
 Light gry, med-fine gr ss, carb sh & coal
 Med-dark gry, fine gr ss, carb sh & coal
 Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation
 Dark gry carb sh.
 Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh
 Wt to lt buff to med grn sl carb bent
 Highly calc gry sh w/thin lmst.
 Dk gry shale, fossil & carb w/pyrite incl.
 Lt to dk gry foss carb sl calc sl silty
 ss w/pyrite incl thin sh bands clay & shale breaks

Ojo Alamo	1506'
Kirtland	1569'
Fruitland	2405'
Pic.Cliffs	2787'
Lewis	2932'
Huerfanito Bent.	3527'
Chacra	3791'
Mesa Verde	4304'
Menefee	4595'
Point Lookout	5121'
Mancos	5515'
Gallup	6342'
Greenhorn	7079'
Graneros	7131'
Dakota	7185'