District # 3

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	NOTICE OF IN CHEMICAL	TENTION TO LY TREAT W		R
NOTICE OF INTENTION TO CHANGE PLANS	The state of the s	NOTICE OF IN OTHERWIS	TENTION TO SE ALTER CA		V
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INT	TENTION TO 1	PLUG WELI	
NOTICE OF INTENTION TO DEEPEN WELL					
Chama Ne	w Mexic		August 29,	1940	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:		Piace			Date
Following is a notice of intention to do certain wo thwestern Exploration Co. Penn Bui					<u> </u>
Company or Operator Lea	5 0		Well N Wildcat	200	in C -
of Sec. 35 , T.28N , R4E	——, Þ	N. M. P. M.,	HTTGGG		
FOLLOW INSTRUCTIONS IN THE F	f on 6	7fest of 10 m	ons of the courfect pi	pe by dry	ving veight
FOLLOW INSTRUCTIONS IN THE F FF intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe	f on 6'	AND REGULATION 7feet of 10 m Pipe is 40 la comented wi	ons of the courfect pi	pe by dry	ving veight
FOLLOW INSTRUCTIONS IN THE PARTY Intend to test shut-of the hole and testing pipe for any le	f on 6'	AND REGULATION 7feet of 10 m Pipe is 40 la comented wi	ons of the courfect pi	pe by dry	ving veight
FOLLOW INSTRUCTIONS IN THE F FF intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe	f on 6'	AND REGULATION 7feet of 10 m Pipe is 40 la comented wi	ons of the courfect pi	pe by dry	ving veight
FOLLOW INSTRUCTIONS IN THE F FF intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe	f on 6'	AND REGULATION 7feet of 10 m Pipe is 40 la comented wi	ons of the courfect pi	pe by dry	ving veight
FOLLOW INSTRUCTIONS IN THE F FF intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe	f on 6'	AND REGULATION 7feet of 10 m Pipe is 40 la comented wi	ons of the courfect pi	pe by dry	ving veight
FOLLOW INSTRUCTIONS IN THE Intend to test shut-of the hole and testing pipe for any lews run to the total depth of 67 fer liburton. The casing is set in Manda Contember 1	f on 6' aks. et and	AND REGULATION Tipe is 40 11 comented willer.	ons of the courfect pi	foot in w	ring reight nt by
FOLLOW INSTRUCTIONS IN THE F THE intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe liburton. The casing is set in Mano	fules A fon 6' aks.	AND REGULATION Tipe is 40 11 comented willer.	ons of the court of the the 60 sacks	pe by dry foot in w	ring reight nt by
FOLLOW INSTRUCTIONS IN THE F THE intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe liburton. The casing is set in Mand	f on 6' aks. et and	AND REGULATION OF THE AND REGULATION OF THE AND REGULATION OF THE AND ADDRESS OF THE AND ADDRESS OF THE AND ADDRESS OF THE AND ADDRESS OF THE	ons of the surface pions to the change of the company or company or company or company or constant of the company or constant	pe by dry foot in w	ring reight nt by
FOLLOW INSTRUCTIONS IN THE F THE intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe liburton. The casing is set in Mand	f on 6' aks. et and	AND REGULATION 7feet of 10 me Pipe is 40 11 comented with least southwest. By Position Party	surface pi es, to the th 60 sacks	foot in work of cemer	ring reight nt by
FOLLOW INSTRUCTIONS IN THE F THE intend to test shut-of the hole and testing pipe for any le was run to the total depth of 67 fe liburton. The casing is set in Mand	f on 6' aks. et and	AND REGULATION 7feet of 10 me Pipe is 40 11 comented with least southwest. By Position Party	ons of the surface pins to the control Explorations or Company or	foot in word composition Composition	ring reight nt by