

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 02854

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Carracas Mesa Unit

8. FARM OR LEASE NAME

9. WELL NO.

Carracas Mesa Unit #1-26

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 26, T32N, R5W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
2. NAME OF OPERATOR Belco Petroleum Corporation		7116' KB
3. ADDRESS OF OPERATOR P.O. Box 250 - Big Piny, Wyoming 83113		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8833'	Perforations:	8581'-83'	4 HFF - Squeezed
PBD 8461'		8588'-92'	4 HFF - Squeezed
		8668'-72'	4 HFF - Squeezed
		8727'-31'	4 HFF - Squeezed
		8806'-10'	4 HFF - Squeezed
		8816'-20'	4 HFF - Squeezed

Propose to shoot off 4 1/2", 11.69 casing at free point (Calculated TOC @ 7850') and pull out of hole. Will equalize abandonment cement plugs as follows:

Plug No. 1	35 sacks	50' in and 50' out of casing stub.
Plug No. 2	50 sacks	6550'-6450'
Plug No. 3	75 sacks	3850'-3650'
Plug No. 4	35 sacks	3300'-3200'
Plug No. 5	50 sacks	325'-up
Plug No. 6	5 sacks	@ surface with marker

Will install standard dry hole marker and clean location for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

District Engineer

DATE

May 18, 1968

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 17 1968

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.