Form 3160-5 (April 2004)

Approved by

UNITED STATES • DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO 1004-0137 Expires March 31, 2007

	Lift Co	,,,,,,,,
_	 	
T	 Camal M	_

Date

NMSF-065546B

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for abandoned well. Use For		f Indian, Allottee or Tribe Name 7 JUL -2 PH 12: 28				
SUBMIT IN TRIPLICATE -		7 If Unit or CA/Agreement, Name and/or No. NMNM-73884				
1 Type of Well Oil Well X Gas Well Other 2 Name of Operator XTO Energy Inc.	HUE					
3a Address 2700 Farmington Ave., Bldg. K. Ste 4 Location of Well (Footage, Sec., T., R., M., or Survey, 1975' FSL & 665' FWL SEC 29L-T28N-	3b. Phone No (<i>include area code</i>) 505-324-1090					
12. CHECK APPROPRIATE	BOX(ES) TO INDI	CATE NATURE OF I				
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent X Subsequent Report Final Abandonment Notice 13 Describe Proposed or Completed Operation (clearly lift the proposal is to deepen directionally or recompactation the Bond under which the work will be perfollowing completion of the involved operations. It testing has been completed. Final Abandonment determined that the final site is ready for final insper	plete horizontally, give sui rformed or provide the B If the operation results in Notices shall be filed only	s, including estimated starting bourface locations and mean ond No on file with BLM, a multiple completion or r	sured and true vertical (/BIA. Required subsequence on pletion in a new in	Well Integrity X Other TD & SET PROD CSG d work and approximate duration thereof depths of all pertinent markers and zones, usent reports shall be filed within 30 days atterval, a Form 3160-4 shall be filed once		
XTO Energy Inc. drilled 7-7/8" ho 6860' on 6/21/07 & cemented lst spps Poly-E-flake (12.4 ppg & 1.9 pps Gilsonite & 0.3% Halad-9 (13. w/510 sx 65/35 Type G cement w/6% cuft/sx) f/b 100 sx Type III neat Finished cement job on 6/21/07. **Production casing will be tested	stage w/255 sx 65 cuft/sx) f/b 175 5 ppg & 1.32 cuft Bentonite, 5 pp c cement (14.5 pp	/35 Type G cement sx 50/50 Type G ot/sx). Circ bbls s Gilsonite & 1/4 g & 1.38 cuft/sx)	w/6% Bentonite cement w/3% Ben cement to surf pps Poly-E-fla	, 5 pps Gilsonite, & 1/4 tonite, 0.1% CFR-3, 5 . Cemented 2nd stage ke (12.4 ppg & 1.9		
14 I hereby certify that the foregoing is true and correct		Title		JUL 0 5 207 FARMINGTON FIELD OFFICE BY IL SALVETS		
Name (Printed/Typed) LORRY D. BINGHAM	REGULA	TORY COMPLIANCE	TECH			
W. Jusan		Date 6/29/07				

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Tıtle