

Form 9-551
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

REMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
D. LEASE DESIGNATION AND SERIAL NO.

NM 03603-A

G. IF INDIAN, ALIQUOT OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS


(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Great Lakes Chemical Corporation	8. PART OR LEASE NAME Hammond
3. ADDRESS OF OPERATOR Minerals Management Inc., Suite 105, 501 Airport Drive, Farmington, New Mexico 87401	9. WELL NO. 5
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde
11. SEC. T. R. M. OR B.L. AND SURVEY OR AREA SEC. 35, T27N, R8W	12. COUNTY OR PARISH NMPM
13. STATE San Juan	14. PERMIT NO. 1840' FNL, 1750' FWL, SEC. 36, T27N, R8W
15. ELEVATIONS (Show whether of, to, or, etc.) 6110' GR, 6122' KB	16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRAC TURE TREAT	☐	FRAC TURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other) Production Casing	☒
(Other)	☐	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. TO BE FILLER PROVIDED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12-2-77 Ran 146 jts (4678') 4 1/2", 10.5#, K-55, ST&C casing set at 4688' KB and cemented in two stages. First stage: 465 sx Halliburton Light, 10# Gilsonite/sx tailed with 100 sx Class "B", 10% salt. Plug down at 9:45 p.m. Opened DV tool and circulated cement. Second stage: 630 sx Halliburton Light, 10# Gilsonite/sx tailed with 50 sx Class "B", 10% salt. Plug down at 2:45 a.m., 12-3-77. Circulated cement.



18. I hereby certify that the foregoing is true and correct
SIGNED [Signature] TITLE Area Manager
Minerals Management Inc. 12-5-77
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE RECEIVED _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

DEC 6 1977
U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.