

63-30-045-11177

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

228-30-045-27600

NORTHWESTERN NEW MEXICO

03572

27600

Operator Meridian Oil Inc Location: Unit 6 Sec. 36 Twp 32 Rng 9

Name of Well/Wells or Pipeline Serviced San Juan 35-9 #228 and

San Juan 35-9 #63

Elevation Completion Date 7-21-91 Total Depth 365 Land Type F

Casing Strings, Sizes, Types & Depths Set 100' of 8" P.U.C.

If Casing Strings are cemented, show amounts & types used 20' sacks
of neat cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Water at 140' and clear

Depths gas encountered: No gas

Ground bed depth with type & amount of coke breeze used: 365' with
50 sacks of Loresco SW

Depths anodes placed: #1 is at 350' and #2 is at 180'

Depths vent pipes placed: 365'

Vent pipe perforations: Up to 150'

Remarks:

RECEIVED

FEB 24 1992

OIL CON. DIV.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 03510 2506-4	P/L NAME(s), NUMBER(s) S.J. 32-9 #228, #63					
2411	TOTAL	VOLTS 12.97	AMPS 18.5	- OHMS	DATE	NAME

REMARKS (notes for construction log)

Vent pipe is perforated to 100'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100	1.5		295	1.0		490			685			
105	1.3		300	.4		495			690			
110	.8		305	.3		500			695			
115	.7		310	.5		505			700			
120	1.6		315	.5		510			ANODE	DEPTH	NO.	FULLY
125	1.9		320	.7		515			*		COKE	COKE'D
130	1.3		325	1.5 (3)		520			1	350	1.6	3.3
135	.7		330	5.2		525			2	335	1.5	4.3
140	.3		335	1.0 (2)		530			3	325	1.5	4.0
145	.3		340	.7		535			4	290	1.5	4.5
150	1.3		345	1.1		540			5	380	2.2	5.2
155	.7		350	1.7 (1)		545			6	270	1.7	5.3
160	.5		355	1.7		550			7	260	1.6	5.1
165	.5		360	1.7		555			8	350	1.8	5.1
170	.6		365	TD		560			9	220	1.3	4.6
175	.7		370			565			10	210	2.0	3.9
180	1.4 (2)		375			570			11	200	1.5	5.1
185	1.1		380			575			12	180	1.4	3.7
190	.6		385			580			13			
195	.7		390			585			14			
200	1.4 (1)		395			590			15			
205	1.9		400			595			16			
210	5.0 (10)		405			600			17			
215	2.1		410			605			18			
220	1.6 (9)		415			610			19			
225	1.4		420			615			20			
230	.5		425			620			21			
235	.5		430			625			22			
240	.5		435			630			23			
245	1.4		440			635			24			
250	1.8 (8)		445			640			25			
255	1.6		450			645			26			
260	1.1 (7)		455			650			27			
265	1.7		460			655			28			
270	1.7 (6)		465			660			29			
275	1.6		470			665			30			
280	2.3 (5)		475			670						
285	2.0		480			675						
290	1.4 (4)		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy

- Division Correction Supervisor

copy

- Region Correction Specialist