

E

775

7- 30-045-08255

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 13 Twp 29 Rng 10

Name of Well/Wells or Pipeline Serviced NEUDECKER #7

cps 1032w

Elevation 5855' Completion Date 6/66 Total Depth 160' Land Type* N/A

Casing, Sizes, Types & Depths 10'

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 2400 lbs.

Depths anodes placed: 155', 145', 140', 130', 125'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: qb #1

RECEIVED
MAY 8 1/1991
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

COMPANY LA PLATA GATHERING CO JOB No. 3271 DATE: JUNE 1966
 WELL: HERRIN # 1-73 Neudecker⁷ PIPELINE:
 LOCATION: SEC. 13 TWP. 29 RGE. 10 CO. SAN JUAN STATE N. MEX.
 ELEV. _____ FT: ROTARY 160 FT: CABLE TOOL 40 FT: CASING 40 FT.
 GROUNDBED: DEPTH 160 FT. DIA. 6 3/4 IN. GAB 2400 LBS. ANODES 6-1 1/2" x 60" D-51

DEPTH, FT.	DRILLER'S LOG	DRILL PIPE TO STRUCTURE			EXPLORING ANODE TO STRUCTURE			DEPTH, TOP OF ANODES
		E	I	R	E	I	R	
	CASING							
10								
20								
30								
40								
	SANDSTONE	12.0	6.0		12.0	0.4		
50						0.4		
60			8.0			0.4		
70	SANDY SHALE					1.0		
80	SAND STONE		12.0			1.0		
	BLUE SHALE					0.9		
90			15.0			1.2		
100						1.3		
			17.0			1.3		
10	BLUE SANDY SHALE					1.4		
20			25.0			1.4		115
30								125
	BLUE SHALE		27.0			1.3		130
40						1.3		140
50			30.0			1.3		145
60		12.0	31.0		12.0	1.4		155

2400 # C&P

36 #

58551

GROUNDED RESISTANCE: (1) VOLTS 13 + AMPS 7.5 = 1.7 OHMS(2) VIBROGROUND 1.6 OHMS

cathodic protection service

HOUSTON TEXAS