

549

24-30-045-06030
60-30-045-06015

E 1015W

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit K Sec. 4 Twp. 26 Rng. 9Name of Well/Wells or Pipeline Serviced Huerfano #60, #54Elevation 207 Completion Date 11-27-91 Total Depth 363 Land Type FCasing Strings, Sizes, Types & Depths Set 700' of 8" P.J.C.If Casing Strings are cemented, show amounts & types used Used 23
sacks of neat cement.If Cement or Bentonite Plugs have been placed, show depths & amounts used
No plugsDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. H₂O is at 130' and clearDepths gas encountered: No gasGround bed depth with type & amount of coke breeze used: 363' with
51 sacks of Asbury 4518Depths anodes placed: #1 is at 345' & #12 is at 145'Depths vent pipes placed: 363 to surfaceVent pipe perforations: perforated up to 140'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					
1015-W	Huertanito #24 #60					
NO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
		1172	28.9		11-27-91	R. Smith
REMARKS (notes for construction log)						
H ₂ O is at 130' Jent - 140						
DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH
	ANODE	#		ANODE	#	
100	2.1		295	1.8		490
105	2.1		300	1.7		495
110	2.2		305	1.3		500
115	2.0		310	1.0		505
120	2.0		315	1.3		510
125	2.1		320	2.1		515
130	2.1		325	2.3	(B)	520
135	2.2		330	2.2		525
140	2.2		335	2.1	(B)	530
145	2.3	(B)	340	2.1		535
150	2.4		345	2.2	(D)	540
155	2.2	(D)	350	1.9		545
160	2.0		355	1.9		550
165	2.1	(D)	360	1.9		555
170	2.3		365	TD36B		560
175	2.2	(D)	370			565
180	2.2		375			570
185	2.6	(B)	380			575
190	2.7		385			580
195	2.4	(D)	390			585
200	2.0		395			590
205	1.6		400			595
210	1.1		405			600
215	1.5		410			605
220	1.3		415			610
225	.9		420			615
230	.9		425			620
235	1.3		430			625
240	2.0		435			630
245	2.3	(B)	440			635
250	2.4		445			640
255	2.1	(B)	450			645
260	2.3		455			650
265	2.1	(B)	460			655
270	1.7		465			660
275	1.7		470			665
280	1.4		475			670
285	1.2		480			675
290	1.4		485			680
						685
						690
						695
						700
						ANODE
						DEPTH
						NO
						COKE
						FULLY
						COKE D
						1
						2
						3
						4
						5
						6
						7
						8
						9
						10
						11
						12
						13
						14
						15
						16
						17
						18
						19
						20
						21
						22
						23
						24
						25
						26
						27
						28
						29
						30

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist