

1- 30-045-08245
7- 30-045-20908 4602
- 201- 30-045-26986

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit M Sec. 17 Twp 29 Rng 8

Name of Well/Wells or Pipeline Serviced DAY #1, DAY #7, DAY #201

cps 80w

Elevation 6400' Completion Date 7/30/87 Total Depth 400' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 180' & 280'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

OIL CON. DIV
DIST. 3

Type & amount of coke breeze used: N/A

Depths anodes placed: 345', 335', 325', 315', 305', 295', 255', 225', 215', 205'

Depths vent pipes placed: 380' OF 1" VENT PIPE

Vent pipe perforations: BOTTOM 200'

Remarks: gb #3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING CATHODIC PROTECTION CONSTRUCTION REPORT DAILY LOG

Drilling Log (Attach Hereto) ☐Completion Date 7-30-87

already in computer

CPS #	Well Name, Line or Plant	Work Order #	State:	Ins Union Check
80-w	DAY #1 DAY #7			☒ Good ☐ Bad
Location	Anode Size	Anode Type	Size Bit	
SW 17-29-8	2" x 60"	Duriron	6 3/4"	
Depth Drilled	Depth Logged	Drilling Rig Time	Total Lbs. Coke Used	Lost Circulation Mat. Used
400'	380'			
Anode Depth				
# 1 345'	# 2 335'	# 3 325'	# 4 315'	# 5 305'
# 6 295'	# 7 255'	# 8 225'	# 9 215'	# 10 205'
Anode Output (Amps)				
# 1 2.8	# 2 3.7	# 3 3.2	# 4 3.3	# 5 3.2
# 6 2.8	# 7 3.1	# 8 2.9	# 9 2.9	# 10 4.0
Anode Depth				
# 11	# 12	# 13	# 14	# 15
# 16	# 17	# 18	# 19	# 20
Anode Output (Amps)				
# 11	# 12	# 13	# 14	# 15
# 16	# 17	# 18	# 19	# 20
Total Circuit Resistance	No. 8 C.P. Cable Used		No. 2 C.P. Cable Used	
Volts 12.5	Amps 15.7	Ohms .80	ELEVATION = 6382	

Remarks: Drilled to 400'; LOGGED 380'. DRILLER SAID WATER AT 180' & 280' BUT NOT ENOUGH FOR SAMPLE. INSTALLED 38' OF 1" PVC VENT PIPE; PERFORATED BOTTOM 200' OF VENT PIPE

Rectifier Size: _____ V _____ A
 Addn'l Depth: _____
 Depth Credit: 120' ✓
 Extra Cable: 10' ✓
 Ditch & 1 Cable: 60'
 Ditch & 2 Cable: _____
 25' Meter Pole: _____
 20' Meter Pole: _____
 10' Stub Pole: _____
 Junction Box: _____

All Construction Completed

Mah R. Williams
 (Signature)

4300. ✓
 - 480. ✓
 2.50 ✓
 23.40 ✓
 40.00 ✓
 3885.90
 194.30
 \$ 4080.20

NEW G.B.

OF --- 80w

110
DAY #1

LATERAL C-61

TK A5

TK A5 LOOP

110
DAY #7

N

Tool Dresser

