

657

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

30-039-24361

Operator Meridian Oil Location: Unit N Sec. 2 Twp 31 Rng 6Name of Well/Wells or Pipeline Serviced Rosa #239Elevation 346 Completion Date 10-23-91 Total Depth 420' Land Type FCasing Strings, Sizes, Types & Depths 60' 40' 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NODepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry holeRECEIVED
FEB 24 1992Depths gas encountered: NOOIL CON. DIV.
DIST. 3

Ground bed depth with type & amount of coke breeze used:

420' Ashbury 69 sacksDepths anodes placed: 400' 350' 370' 310' 295' 280' 265' 255' 245' 235' 225' 215' 145' 15'Depths vent pipes placed: 380'Vent pipe perforations: 1' apart Perforated bottom 280' fromRemarks: 2nd anode!

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2286	P/L NAME(s), NUMBER(s) Loss # 239					
WO # L178	TOTAL	VOLTS 12.46	AMPS 23.0	OHMS .54	DATE 10-23-91	NAME L.S.E.
REMARKS (notes for construction log)						
NO Water Table, Dry hole. Set 60' of 8" PVC casing. Perforated bottom 280' from 2" anode.						

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100	1.1		295	2.6	-5	490			685			
105	.9		300	2.5		495			690			
110	.7		305	2.7		500			695			
115	.6		310	2.7	-4	505			700			
120	.6		315	2.4		510			ANODE	DEPTH	NO	FULLY
125	.8		320	2.0		515			*		COKE	COKE'D
130	.9		325	2.0		520			1	400	2.4	4.3
135	2.1		330	1.7		525			2	380	2.3	4.3
140	2.8		335	1.5		530			3	370	2.3	4.1
145	2.8	-15	340	1.7		535			4	310	2.8	4.7
150	2.9		345	1.9		540			5	295	2.6	4.6
155	2.7	-14	350	2.0		545			6	280	2.4	4.8
160	2.8		355	1.8		550			7	265	3.1	5.3
165	2.5	-13	360	1.8		555			8	255	3.0	5.5
170	2.3		365	2.1		560			9	245	2.7	5.2
175	1.8		370	2.2	-3	565			10	235	2.8	5.4
180	1.7		375	2.3		570			11	225	2.5	5.2
185	1.9		380	2.1	-2	575			12	215	2.6	5.0
190	1.0		385	1.9		580			13	165	2.5	4.8
195	.9		390	1.9		585			14	155	2.7	5.4
200	1.1		395	1.9		590			15	145	2.9	5.7
205	2.0		400	2.4	-1	595			16			
210	2.3		405	2.1		600			17			
215	2.6	-12	410	1.9		605			18			
220	2.3		415	2.0		610			19			
225	2.5	-11	420	1.5	T.D.	615			20			
230	2.5		425			620			21			
235	2.7	-10	430			625			22			
240	2.9		435			630			23			
245	2.7	-9	440			635			24			
250	2.6		445			640			25			
255	2.9	-8	450			645			26			
260	3.0		455			650			27			
265	3.1	-7	460			655			28			
270	2.5		465			660			29			
275	2.2		470			665			30			
280	2.4	-6	475			670						
285	2.4		480			675						
290	2.5		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist