

661
30-039-24984
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meredian Oil Location: Unit M Sec. 21 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced Lusa # 263

Elevation 6802 Completion Date 9-24-91 Total Depth 395 Land Type F

Casing Strings, Sizes, Types & Depths 60" sch 40 8' PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV. 1

DIST. 3

Ground bed depth with type & amount of coke breeze used:

395' Ashbury 64 sacks

Depths anodes placed: 375, 360, 345, 330, 315, 300, 287, 264, 249, 230, 215, 200

Depths vent pipes placed: 360'

Vent pipe perforations: 1" apart, Perforated bottom 260'

Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					
2290-W	Loss # 263					
WO #	TOTAL	VOLTS	AMPS	OHMS	DATE	NAME
L484		12.38	31.8	.39	9-24-91	L.S.E.
REMARKS (notes for construction log)						
Mount 130' NO water table, Dry hole Set 60' of 8" PVC casing. Perforated bottom 260' from 2" anode.						

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100	1.2		295	4.0		490			685			
105	1.6		300	4.0	-6 R	495			690			
110	3.3		305	3.9		500			695			
115	3.4		310	3.9		505			700			
120	3.0		315	4.0	-5 R	510			ANODE	DEPTH	NO.	FULLY
125	2.5		320	4.0		515			*		COKE	COKE D
130	1.3		325	3.8		520			1	375	4.2	7.1
135	2.1		330	4.0	-4 R	525			2	360	4.2	7.5
140	3.6		335	4.1		530			3	345	4.3	7.2
145	4.2		340	4.1		535			4	330	4.1	6.9
150	3.9		345	4.1	-3 R	540			5	315	4.1	7.2
155	3.5		350	4.3		545			6	300	4.1	7.4
160	3.6		355	4.4		550			7	287	3.6	6.8
165	3.9		360	4.3	-2 R	555			8	264	4.1	6.8
170	3.7		365	3.9		560			9	249	4.3	7.4
175	3.7		370	4.4		565			10	230	4.1	7.6
180	3.6		375	4.1	-1 R	570			11	215	4.1	8.1
185	3.6		380	3.3		575			12	200	4.2	8.2
190	3.4		385	3.7		580			13			
195	3.9		390	3.7		585			14			
200	4.1	-12 R	395	TD	395	590			15			
205	3.5		400			595			16			
210	3.3		405			600			17			
215	4.3	-11 R	410			605			18			
220	4.2		415			610			19			
225	3.9		420			615			20			
230	3.9	-10 R	425			620			21			
235	2.9		430			625			22			
240	3.4		435			630			23			
245	4.3		440			635			24			
250	3.8	-9 R	445			640			25			
255	4.1		450			645			26			
260	4.0		455			650			27			
265	3.8	-8 R	460			655			28			
270	3.5		465			660			29			
275	3.2		470			665			30			
280	3.3		475			670						
285	3.6	-7 R	480			675						
290	4.2		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist