

655

30-039-24425

8

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit 4 Sec. 30 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced Losa = 223

2282W

Elevation 6360 Completion Date 11-8-91 Total Depth 434' Land Type F

Casing Strings, Sizes, Types & Depths 60' 4" 40' 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV.
DIST. 3

Ground bed depth with type & amount of coke breeze used:

434' Ashless 72 sacks

Depths anodes placed: 415' 395' 380' 365' 355' 320' 310' 300' 290' 265' 240' 230'

Depths vent pipes placed: 395'

Vent pipe perforations: 1" apart perforated bottom 250'

Remarks: from 2nd anode

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					
2282	Loss # 223					
NO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
M 278		12.49	20.8	.60	11-8-91	L.S.E.

REMARKS (notes for construction log)

No Water table. Dry hole. Set 60' of 8" PVC casing. Perforated bottom 250' from 2nd anode.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100	1.9		295	2.0		490			685			
105	1.9		300	2.1	- 5	495			690			
110	1.6		305	1.7		500			695			
115	1.4		310	2.1	- 7	505			700			
120	2.0		315	2.4		510			ANODE	DEPTH	NO	FULLY
125	2.1		320	2.6	-	515			*		COKE	COKE'D
130	2.7		325	1.8		520			1	415	2.4	5.1
135	2.6		330	1.3		525			2	395	2.0	4.3
140	2.4		335	1.2		530			3	380	2.3	4.8
145	3.0		340	1.2		535			4	365	2.2	4.9
150	3.1		345	1.6		540			5	355	2.3	5.0
155	2.0		350	1.7		545			6	320	2.5	5.1
160	1.8		355	2.2	- 5	550			7	310	2.2	5.1
165	2.8		360	2.5		555			8	300	2.1	5.0
170	3.0		365	2.0	- 4	560			9	290	2.3	4.9
175	2.2		370	1.7		565			10	265	2.3	4.4
180	2.1		375	1.5		570			11	240	2.4	5.0
185	2.6		380	2.3	- 3	575			12	230	2.7	5.4
190	2.4		385	2.0		580			13			
195	1.9		390	1.8		585			14			
200	1.9		395	2.0	- 2	590			15			
205	1.8		400	1.9		595			16			
210	1.8		405	1.9		600			17			
215	1.9		410	2.1		605			18			
220	2.0		415	2.3	- 1	610			19			
225	2.1		420	2.8		615			20			
230	2.7	- 12	425	2.6		620			21			
235	2.9		430	2.2		625			22			
240	2.4	- 11	435	T.D	434	630			23			
245	1.6		440			635			24			
250	1.5		445			640			25			
255	1.6		450			645			26			
260	2.0		455			650			27			
265	2.1	- 10	460			655			28			
270	1.6		465			660			29			
275	1.7		470			665			30			
280	1.6		475			670						
285	2.2		480			675						
290	2.3	- 9	485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist