

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2007 JUL 18 PM 3:01

RECEIVED 5.

BLM
2107 FARMINGTON NM

1. Type of Well
GAS

Lease Number
SF-080854
If Indian, All. or
Tribe Name

2. Name of Operator
ConocoPhillips

7. Unit Agreement Name

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. San Juan 32-8 Unit
Well Name & Number

9. SJ 32-8 Unit #29M
API Well No.

4. Location of Well, Footage, Sec., T, R, M

Unit P (SESE) 661' FSL & 1097' FEL, Sec. 11, T31N, R8W, NMPM

30-045-34075

10. Field and Pool

Blanco Mesa Verde/Basin DK

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☐ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection

13. Describe Proposed or Completed Operations

7/6/07 NU BOPE. RIH w/8-3/4" bit, tagged cement @ 205'. Drilled ahead to 3885' intermediate. Circ hole. RIH w/7" 20# J-55 ST & C casing set @ 3869'. RU to cement. 7/10/07 Pumped pre-flush of 10 bbls FW/10 bbls mud clean/10 bbls FW. Pumped Scavenger 20 sx(60cf-11bbls) Class G Cement w/3% CaCl₂, .25 #/sx Cello-Flake, 8% FL-52, .5#/sx LCM-1, .4% SMS. Lead-pumped 510 sx (1086cf-193bbls) Premium Lite Cement w/3% CaCl₂, .25 #/sx Cello-Flake, 8% FL-52, .5 #/sx LCM-1, & .4% SMS. Tail-pumped 100 sx(138cf-25bbls) Type III Cement w/1% CaCl₂, .25 #/sx Cello-Flake, & 8% FL-52. Dropped plug & displaced w/155 bbls FW. Bumped plug to 1600#. Circ 60 bbls cement to pit. ✓

7/11/07 RIH w/6-1/4" bit. PT casing to 1500# 30/min - good test. ✓ Drilled ahead to 8219' (TD). TD reached on 7/13/07. Circ hole. RIH w/158 jts 4-1/2" 10.5# J-55 casing & 41 jts 4 1/2" 11.6# J-55 casing set @ 8218'. RU to cement. 7/14/07 pumped pre-flush of 10 bbls gel water/2 bbls FW. Pumped Scavenger 10 sx(30cf-5bbls) Class G Cement. Pumped 320 sx(634cf-113bbls) Premium Lite Cement w/6.25 #/sx CD-32, .25 #/sx Cello-Flake, 1% FL-52A, & 1% LCM-1. Dropped plug & displaced w/120 bbls FW. Bumped Plug to 1500#. Plug down @ 16:34 hrs. WOC. ND, RD, RR @ 2245.

RCVD JUL 25 07

The casing PT & TOC will be conducted by the completion rig and results shown on next report. ✓

OIL CONS. DIV.

DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 7/18/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOC

ACCEPTED FOR RECORD

JUL 23 2007

FARMINGTON FIELD OFFICE

BY T. Salyers