

4948

30-045-09846

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 6 Twp 30 Rng 9

Name of Well/Wells or Pipeline Serviced QUIGLEY #1

cps 44w

Elevation 6510' Completion Date 11/13/61 Total Depth 200' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 1350 lbs.

Depths anodes placed: 173', 167', 161', 130', 124'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: qb #1

RECEIVED
MAY 31 1991

CON DIV
IST 2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

SAN JUAN DIVISION
WELL CASING CATHODIC PROTECTION
DAILY CONSTRUCTION
PROGRESS REPORT

DATE 11-13-61

WELL NAME - Quigley #1 WORK ORDER NO. 184-52293-50-10

NUMBER AND DEPTH OF HOLES: #1 200', #2 , #3 , #4 , #5 .

DEPTH OF EACH ANODE: #1 173', #2 167', #3 161', #4 130', #5 124', #6 , #7
#8 , #9 , #10 .

ANODE RESISTANCES: #1 4.8, #2 4.2, #3 6.8, #4 4.7, #5 5.1, #6 , #7
#8 , #9 , #10 .

TOTAL CIRCUIT RESISTANCE: 2.1 OHMS.

DRILLING LOG: (ATTACH HERETO)

AMOUNT OF COKE BREEZE PLACED IN EACH HOLE: #1 1350 lbs, #2 , #3
#4 , #5 .

ANY DIFFICULTIES ENCOUNTERED IN DRILLING:

ROCKS-

LOST CIRCULATION- 2 hrs lost circulation

CASING INSTALLED-

DATE ALL CONSTRUCTION COMPLETED .

REMARKS:

*Hole taking water fast had water truck
standby while loading hole*

*Place anodes at lowest resistances from
anode log.*

Edward R. Paulk
SIGNATURE OF INSPECTOR

DAILY DRILLING REPORT

19

EVENING

Driller					Total Man in Crew					Driller					Total Man in Crew				
FROM	TO	FORMATION	WT. BIT	R.P.M.	FROM	TO	FORMATION	WT. BIT	R.P.M.	FROM	TO	FORMATION	WT. BIT	R.P.M.					
0	45	SANDY Brown Clay			1.25	1.35	SAND												
45	105	SANDSTONE			1.35	1.70	SANDSTONE												
105	115	SAND			1.70	1.85	SAND												
115	125	SANDSTONE			1.85	2.00	SANDSTONE												
BIT NO.					NO. DC					NO. DC					NO. DC				
SERI. O.					NO. DC					NO. DC					NO. DC				
SIZE					STANDS					STANDS					STANDS				
TYPE					SINGLES					SINGLES					SINGLES				
MAKE					DOWN ON KELLY					DOWN ON KELLY					DOWN ON KELLY				
MUD RECORD					TOTAL DEPTH					TOTAL DEPTH					TOTAL DEPTH				
MUD, ADDITIVES USED AND RECEIVED					MUD, ADDITIVES USED AND RECEIVED					MUD, ADDITIVES USED AND RECEIVED					MUD, ADDITIVES USED AND RECEIVED				
Time					Time					Time					Time				
WT.					WT.					WT.					WT.				
VIS.					VIS.					VIS.					VIS.				
FROM					TO					FROM					TO				
TIME BREAKDOWN					TIME BREAKDOWN					TIME BREAKDOWN					TIME BREAKDOWN				
REMARKS -					REMARKS -					REMARKS -					REMARKS -				
2 sack mud																			
1 sack hulls																			
LOST CIRCULATION FOR 2 HOURS																			