

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144
June 1, 2004

For drilling and production facilities, submit to
appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe
office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐

Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator: BP AMERICA PROD. CO. Telephone: (505)-326-9200 e-mail address: _____
Address: 200 ENERGY COURT, FARMINGTON, NM 87410
Facility or well name: TAPP COM #5E API #: 30-045- 25682 U/L or Qtr/Qtr H Sec 17 T 28N R 8W
County: SAN JUAN Latitude 36.66449 Longitude 107.69985 NAD: 1927 ☐ 1983 ☒ Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

Pit

Type: Drilling ☐ Production ☐ Disposal ☒ DEHYDRATOR

Workover ☐ Emergency ☐

Lined ☒ Unlined ☐ STEEL TANK

Liner type: Synthetic ☐ Thickness _____ mil Clay ☐

Pit Volume _____ bbl

Below-grade tank

Volume: _____ bbl Type of fluid: _____

Construction material: N/A

Double-walled, with leak detection? Yes ☐ If not, explain why not.

Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet	(20 points)	0
	50 feet or more, but less than 100 feet	(10 points)	
	100 feet or more	(0 points)	
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes	(20 points)	0
	No	(0 points)	
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)	0
	200 feet or more, but less than 1000 feet	(10 points)	
	1000 feet or more	(0 points)	
Ranking Score (Total Points)			0

If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you are burying in place) onsite ☒ offsite ☐ If offsite, name of facility _____. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☒ Yes ☐ If yes, show depth below ground surface _____ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments PIT LOCATED APPROXIMATELY 91 FT. S2W FROM WELL HEAD.

PIT EXCAVATION: WIDTH N/A ft., LENGTH N/A ft., DEPTH N/A ft.

PIT REMEDIATION: CLOSE AS IS: ☒ LANDFARM: ☐ COMPOST: ☐ STOCKPILE: ☐ OTHER ☐ (explain)

Cubic yards: N/A

RCUD APR5'07
OIL CONS. DIV.

DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐, or an alternative OCD-approved plan ☒.

Date: 03/10/06

Printed Name/Title Jeff Blagg - P.E. # 11607

Signature Jeff Blagg

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.




Approval:

Deputy Oil & Gas Inspector,
District #3

Printed Name/Title _____

Signature Branch Bell

Date: AUG 01 2007

CLIENT: <u>BP</u>	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	LOCATION NO: <u>B1763</u> COCR NO: <u>15660</u>																																																
FIELD REPORT: PIT CLOSURE VERIFICATION		PAGE No: <u>1</u> of <u>1</u>																																																
LOCATION: NAME: <u>TAPP COM</u> WELL#: <u>SE</u> TYPE: <u>DEHY</u> QUAD/UNIT: <u>H SEC: 17 TWP: 28N RNG: 8W PM: NM CNTY: SJ ST: NM</u> QTR/FOOTAGE: <u>1535 FNL * 1330 FEL SE/NE</u> CONTRACTOR: <u>HDI (LIUWEL)</u>		DATE STARTED <u>3-9-06</u> DATE FINISHED: <u>3-9-06</u> ENVIRONMENTAL SPECIALIST: <u>JCB</u>																																																
EXCAVATION APPROX. <u>NA</u> FT. x <u>NA</u> FT. x <u>NA</u> FT. DEEP. CUBIC YARDAGE: <u>0</u>																																																		
DISPOSAL FACILITY: <u>NA</u> REMEDIATION METHOD: <u>CLOSE AS IS</u>																																																		
LAND USE: <u>RANGE - BLM</u> LEASE: <u>NM 076071</u> FORMATION: <u>DK</u>																																																		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY <u>91</u> FT. <u>S 2 W</u> FROM WELLHEAD.																																																		
DEPTH TO GROUNDWATER: <u>>100</u> NEAREST WATER SOURCE: <u>>1000</u> NEAREST SURFACE WATER: <u>>1000</u>																																																		
NMOC D RANKING SCORE: <u>0</u> NMOC D TPH CLOSURE STD: <u>5000</u> PPM																																																		
SOIL AND EXCAVATION DESCRIPTION:																																																		
SOIL TYPE: <u>SAND</u> / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER _____ SOIL COLOR: <u>Yellow Tan</u> COHESION (ALL OTHERS): <u>NON COHESIVE</u> / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): <u>LOOSE</u> / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY / <u>SLIGHTLY MOIST</u> / MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: YES / <u>NO</u> EXPLANATION - _____ HC ODOR DETECTED: YES / <u>NO</u> EXPLANATION - _____ SAMPLE TYPE: <u>GRAB</u> / COMPOSITE - # OF PTS. _____ ADDITIONAL COMMENTS: <u>6'x6'x6' DEEP WOOD LINED CELLAR w/ 21 BBL STEEL TANK. USE BACKHOE TO RLL TANK & collect sample. NO EVIDENCE OF CONTAMINATION.</u>																																																		
OVM CALIB. READ = <u>53.6</u> ppm OVM CALIB. GAS = <u>100</u> ppm RF = 0.52 TIME: <u>0730</u> am/pm DATE: <u>3/9/06</u>																																																		
FIELD 418.1 CALCULATIONS																																																		
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>SAMP. TIME</th> <th>SAMP. ID</th> <th>LAB NO.</th> <th>WEIGHT (g)</th> <th>mL FREON</th> <th>DILUTION</th> <th>READING</th> <th>CALC. (ppm)</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>			SAMP. TIME	SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)																																								
SAMP. TIME	SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)																																											
SCALE 		PIT PERIMETER 																																																
OVM READING <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>SAMPLE ID</th> <th>FIELD HEADSPACE (ppm)</th> </tr> </thead> <tbody> <tr><td>1 @</td><td> </td></tr> <tr><td>2 @</td><td> </td></tr> <tr><td>3 @</td><td> </td></tr> <tr><td>4 @</td><td> </td></tr> <tr><td>5 @</td><td> </td></tr> <tr><td>C @ 9'</td><td>0.0</td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> </tbody> </table>		SAMPLE ID	FIELD HEADSPACE (ppm)	1 @		2 @		3 @		4 @		5 @		C @ 9'	0.0									PIT PROFILE 																										
SAMPLE ID	FIELD HEADSPACE (ppm)																																																	
1 @																																																		
2 @																																																		
3 @																																																		
4 @																																																		
5 @																																																		
C @ 9'	0.0																																																	
LAB SAMPLES <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>SAMPLE ID</th> <th>ANALYSIS</th> <th>TIME</th> </tr> </thead> <tbody> <tr><td>C @ 9'</td><td>TPH</td><td>1/25</td></tr> <tr><td> </td><td>BTEX</td><td> </td></tr> <tr><td> </td><td>CL</td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table>		SAMPLE ID	ANALYSIS	TIME	C @ 9'	TPH	1/25		BTEX			CL								CLOSED																														
SAMPLE ID	ANALYSIS	TIME																																																
C @ 9'	TPH	1/25																																																
	BTEX																																																	
	CL																																																	
P.D. = PIT DEPRESSION; B.G. = BELOW GRADE, B = BELOW T.H. = TEST HOLE, ~ = APPROX.; T.B. = TANK BOTTOM																																																		
TRAVEL NOTES: CALLOUT: _____ ONSITE: <u>3/9/06</u>																																																		

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / BP	Project #:	94034-010
Sample ID:	C @ 9'	Date Reported:	03-10-06
Laboratory Number:	36422	Date Sampled:	03-09-06
Chain of Custody No:	15660	Date Received:	03-09-06
Sample Matrix:	Soil	Date Extracted:	03-10-06
Preservative:	Cool	Date Analyzed:	03-10-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: **Tapp Com 5 E Dehy Pit.**


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	C @ 9'	Date Reported:	03-10-06
Laboratory Number:	36422	Date Sampled:	03-09-06
Chain of Custody:	15660	Date Received:	03-09-06
Sample Matrix:	Soil	Date Analyzed:	03-10-06
Preservative:	Cool	Date Extracted:	03-10-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	3.2	1.8
Toluene	7.2	1.7
Ethylbenzene	4.3	1.5
p,m-Xylene	37.5	2.2
o-Xylene	6.8	1.0
Total BTEX	59.0	


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Tapp Com 5 E Dehy Pit.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

Chloride

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	C @ 9'	Date Reported:	03-10-06
Lab ID#:	36422	Date Sampled:	03-09-06
Sample Matrix:	Soil	Date Received:	03-09-06
Preservative:	Cool	Date Analyzed:	03-10-06
Condition:	Cool and Intact	Chain of Custody:	15660


Parameter	Concentration (mg/Kg)
-----------	-----------------------


Total Chloride

6.7

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Tapp Com 5E Dehy Pit.


Analyst


Review

15660

san juan reproduction 578-129

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	03-10-06 QA/QC	Date Reported:	03-10-06
Laboratory Number:	36422	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	03-10-06
Condition:	N/A	Analysis Requested:	TPH

	I-Cal Date	I-Cal RF	C-Cal RF	% Difference	Accept. Range
Gasoline Range C5 - C10	02-04-05	9.9739E+002	9.9838E+002	0.10%	0 - 15%
Diesel Range C10 - C28	02-04-05	1.0003E+003	1.0023E+003	0.20%	0 - 15%

Blank Conc. (mg/L - mg/Kg)	Concentration	Detection Limit
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2


Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Range
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%
Diesel Range C10 - C28	ND	ND	0.0%	0 - 30%


Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	Accept. Range
Gasoline Range C5 - C10	ND	250	250	100.0%	75 - 125%
Diesel Range C10 - C28	ND	250	250	100.0%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: QA/QC for Samples 36422 - 36424.


Analyst


Review

Client:	N/A	Project #:	N/A
Sample ID:	03-10-BTEX QA/QC	Date Reported:	03-10-06
Laboratory Number:	36422	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	03-10-06
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF:	%Diff.	Blank Conc	Detect Limit
		Accept. Range 0 - 15%			
Benzene	4.5154E+007	4.5245E+007	0.2%	ND	0.2
Toluene	5.7140E+007	5.7255E+007	0.2%	ND	0.2
Ethylbenzene	4.4822E+007	4.4911E+007	0.2%	ND	0.2
p,m-Xylene	1.0871E+008	1.0892E+008	0.2%	ND	0.2
o-Xylene	5.0228E+007	5.0328E+007	0.2%	ND	0.1


Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept. Range	Detect. Limit
Benzene	3.2	3.1	3.1%	0 - 30%	1.8
Toluene	7.2	7.1	1.4%	0 - 30%	1.7
Ethylbenzene	4.3	4.2	2.3%	0 - 30%	1.5
p,m-Xylene	37.5	37.4	0.3%	0 - 30%	2.2
o-Xylene	6.8	6.7	1.5%	0 - 30%	1.0


Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept. Range
Benzene	3.2	50.0	53.1	99.8%	39 - 150
Toluene	7.2	50.0	57.1	99.8%	46 - 148
Ethylbenzene	4.3	50.0	54.3	100.0%	32 - 160
p,m-Xylene	37.5	100	137	99.8%	46 - 148
o-Xylene	6.8	50.0	56.8	100.0%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for Sample 36422 - 36425.


Analyst


Review