

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Form C-144
June 1, 2004

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐

Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator: BP AMERICA PROD. CO. Telephone: (505)-326-9200 e-mail address: _____
Address: 200 ENERGY COURT, FARMINGTON, NM 87410
Facility or well name: JONES A LS #5A API #: 30-045- 23812 U/L or Qtr/Qtr C Sec 13 T 28N R 8W
County: SAN JUAN Latitude 36.66567 Longitude 107.63503 NAD: 1927 ☐ 1983 ☒ Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

RCVD APR 5 '07

Pit	Below-grade tank
Type: Drilling <input type="checkbox"/> Production <input checked="" type="checkbox"/> Disposal <input type="checkbox"/> COMPRESSOR Workover <input type="checkbox"/> Emergency <input type="checkbox"/> Lined <input checked="" type="checkbox"/> Unlined <input type="checkbox"/> STEEL TANK Liner type: Synthetic <input type="checkbox"/> Thickness _____ mil Clay <input type="checkbox"/> Pit Volume _____ bbl	Volume: _____ bbl Type of fluid: _____ Construction material: <u>N/A</u> Double-walled, with leak detection? Yes <input checked="" type="checkbox"/> If not, explain why not. _____
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet (20 points) 50 feet or more, but less than 100 feet (10 points) 0 100 feet or more (0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes (20 points) No (0 points) 0
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet (20 points) 200 feet or more, but less than 1000 feet (10 points) 0 1000 feet or more (0 points)
Ranking Score (Total Points) 0	

If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you are burying in place) onsite ☒ offsite ☐ If offsite, name of facility _____. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☒ Yes ☐ If yes, show depth below ground surface _____ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments: PIT LOCATED APPROXIMATELY 128 FT. S78W FROM WELL HEAD.

PIT EXCAVATION: WIDTH N/A ft., LENGTH N/A ft., DEPTH N/A ft.

PIT REMEDIATION: CLOSE AS IS: ☒ LANDFARM: ☐ COMPOST: ☐ STOCKPILE: ☐ OTHER ☐ (explain)

Cubic yards: N/A

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐, or an alternative OCD-approved plan ☒.

Date: 12/6/06

Printed Name/Title Jeff Blagg - P.E. # 11607

Signature _____

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval: Deputy Oil & Gas Inspector,
Printed Name/Title District #3

Signature _____

Date: AUG 03 2007

30-045-23812

36.66567 * 10 1.65503

CLIENT:

BP

BLAGG ENGINEERING, INC.
P.O. BOX 87, BLOOMFIELD, NM 87413
(505) 632-1199

LOCATION NO: 80998

COCR NO: 1799

FIELD REPORT: PIT CLOSURE VERIFICATION

PAGE No: 1 of 1

LOCATION: NAME: JONES A LS WELL#: 5A TYPE: COMPR.

QUAD/UNIT: C SEC: 13 TWP: 28N RING: SW PM: NM CNTY: SJ ST: NM

QTR/FOOTAGE: 1120 FUL x 1815 FUL NEINW CONTRACTOR: HDI - EDGAR

DATE STARTED: 11-28-06

DATE FINISHED: 11-28-06

ENVIRONMENTAL SPECIALIST: JCB

EXCAVATION APPROX. NA FT. x NA FT. x NA FT. DEEP. CUBIC YARDAGE: 0

DISPOSAL FACILITY: NA REMEDIATION METHOD: CLOSE AS IS

LAND USE: RANGE - 3LM LEASE: 5F-078390 FORMATION: MV

FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 126 FT. S78W FROM WELLHEAD.

DEPTH TO GROUNDWATER: >1000 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000

NMOCD RANKING SCORE: 0 NMOCD TPH CLOSURE STD: 5000 PPM

SOIL AND EXCAVATION DESCRIPTION:

OVM CALIB. READ. = 52.2 ppm
 OVM CALIB. GAS = 100 ppm RF = 0.52
 TIME: 1015 am/pm DATE: 11-28-06

SOIL TYPE SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER

SOIL COLOR TAN

COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVECONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE

PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC

DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD

MOISTURE DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATEDDISCOLORATION/STAINING OBSERVED: YES / NO / EXPLANATION -HC ODOR DETECTED YES / NO / EXPLANATION -SAMPLE TYPE GRAB / COMPOSITE / # OF PTS. 3

ADDITIONAL COMMENTS:

21 BBL steel tank set in 9'x9'x6' hole -
 BASE EXPOSED - SAMPLE W/ BASELINE

SAMPLE PER
 BP POLICY ONLY

CLOSED

SCALE




0 1 FT

FIELD 418.1 CALCULATIONS

SAMP. TIME	SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)

PIT PERIMETER


PIT PROFILE

OVM
READING

SAMPLE ID	FIELD HEADSPACE (ppm)
1 @	
2 @	
3 @	
4 @	
5 @	
3-PT @ 9'	0.0

LAB SAMPLES

SAMPLE ID	ANALYSIS	TIME
3-PT	T/B/C/L	0455

PASSED

PD = PIT DEPRESSION; B.G. = BELOW GRADE, B = BELOW
 TH = TEST HOLE, ~ = APPROX., T.B. = TANK BOTTOM

TRAVEL NOTES:

CALLOUT:

ONSITE:

11-28-06

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / BP	Project #:	94034-010
Sample ID:	3 - Point @ 9'	Date Reported:	11-29-06
Laboratory Number:	39305	Date Sampled:	11-28-06
Chain of Custody No:	1799	Date Received:	11-28-06
Sample Matrix:	Soil	Date Extracted:	11-29-06
Preservative:	Cool	Date Analyzed:	11-29-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	0.9	0.1
Total Petroleum Hydrocarbons	0.9	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: **Jones A LS 5A Compressor Pit**


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	3 - Point @ 9'	Date Reported:	11-29-06
Laboratory Number:	39305	Date Sampled:	11-28-06
Chain of Custody:	1799	Date Received:	11-28-06
Sample Matrix:	Soil	Date Analyzed:	11-29-06
Preservative:	Cool	Date Extracted:	11-29-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	1.8
Toluene	3.6	1.7
Ethylbenzene	7.7	1.5
p,m-Xylene	29.8	2.2
o-Xylene	13.3	1.0
Total BTEX	54.4	


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Jones A LS 5A Compressor Pit


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

Chloride


Client:	Blagg / BP	Project #:	94034-010
Sample ID:	3 - Point @ 9'	Date Reported:	11-29-06
Lab ID#:	39305	Date Sampled:	11-28-06
Sample Matrix:	Soil	Date Received:	11-28-06
Preservative:	Cool	Date Analyzed:	11-29-06
Condition:	Cool and Intact	Chain of Custody:	1799


Parameter	Concentration (mg/Kg)
-----------	-----------------------

Total Chloride	18.0
----------------	------

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Jones A LS 5A Compressor Pit


Analyst


Review

1799

san juan reproduction 578-129

ENVIROTECH LABS

PRactical SOLUTIONS FOR A BETTER TOMORROW

EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	11-29-06 QA/QC	Date Reported:	11-29-06
Laboratory Number:	39305	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	11-29-06
Condition:	N/A	Analysis Requested:	TPH

	I-Cal Date	I-Cal RF	C-Cal RF	% Difference	Accept. Range
Gasoline Range C5 - C10	07-11-05	9.9764E+002	9.9864E+002	0.10%	0 - 15%
Diesel Range C10 - C28	07-11-05	9.9240E+002	9.9439E+002	0.20%	0 - 15%

Blank Conc. (mg/L - mg/Kg)	Concentration	Detection Limit
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2


Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Range
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%
Diesel Range C10 - C28	0.9	0.9	0.0%	0 - 30%


Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	Accept. Range
Gasoline Range C5 - C10	ND	250	250	100.0%	75 - 125%
Diesel Range C10 - C28	0.9	250	250	99.8%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: QA/QC for Samples 39305 - 39310


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	11-29-BTEX QA/QC	Date Reported:	11-29-06
Laboratory Number:	39305	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	11-29-06
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF	C-Cal RF	%Diff Accept. Range 0 - 15%	Blank Conc	Detect. Limit
Benzene	6.1865E+005	6.1989E+005	0.2%	ND	0.2
Toluene	6.3181E+007	6.3307E+007	0.2%	ND	0.2
Ethylbenzene	3.1401E+007	3.1463E+007	0.2%	ND	0.2
p,m-Xylene	1.2258E+008	1.2283E+008	0.2%	ND	0.2
o-Xylene	6.1161E+007	6.1283E+007	0.2%	ND	0.1


Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff	Accept Range	Detect. Limit
Benzene	ND	ND	0.0%	0 - 30%	1.8
Toluene	3.6	3.6	0.0%	0 - 30%	1.7
Ethylbenzene	7.7	7.6	1.3%	0 - 30%	1.5
p,m-Xylene	29.8	29.7	0.3%	0 - 30%	2.2
o-Xylene	13.3	13.2	0.8%	0 - 30%	1.0


Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	ND	50.0	49.9	99.8%	39 - 150
Toluene	3.6	50.0	53.5	99.8%	46 - 148
Ethylbenzene	7.7	50.0	57.6	99.8%	32 - 160
p,m-Xylene	29.8	100	129	99.7%	46 - 148
o-Xylene	13.3	50.0	63.2	99.8%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for Samples 39305 - 39307


Analyst


Review