District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

1220 S. St. Francis Dr., Santa Fe, NM 87505

Deputy Oil & Gas Inspector,

District #3

Approval:

Printed Name/Title

District IV

State of New Mexico **Energy Minerals and Natural Resources**

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

office

AUG 0 9 2007

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank (505)-326-9200 BP AMERICA PROD. CO. e-mail address: Telephone: Address: 200 ENERGY COURT, FARMINGTON, NM 87410 API#: 30-045- 22931 Sec 9 T 30N R 9W Facility or well name: ELLIOTT GC Y #1 H U/L or Qtr/Qtr Longitude 107.78001 County: SAN JUAN Latitude 36.82871 NAD: 1927 1983 Surface Owner Federal State Private Indian RCVD APR5'07 Pit Below-grade tank OIL CONS. DIV. Type: Drilling | Production | Disposal | SEPARATOR Volume: Type-ef-fluid: Construction material DIST. 3 Lined Unlined STEEL TANK Double-walled, with leak catection? Liner type: Synthetic Thickness mil Clay Pit Volume Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 0 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more (0 points) Yes (20 points) Wellhead protection area: (Less than 200 feet from a private domestic 0 No (0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) 0 irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more (0 points) Ranking Score (Total Points) 0 If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if . (3) Attach a general description of remedial action taken including your are burying in place) onsite \(\square\) offsite \(\square\) If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No 🛛 Yes 🗋 If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments PIT LOCATED APPROXIMATELY 81 FT. S88E FROM WELL HEAD. PIT EXCAVATION: WIDTH N/Aft., LENGTH N/Aft., DEPTH N/Aft. PIT REMEDIATION: CLOSE AS IS: ⊠, LANDFARM: □, COMPOST: □, STOCKPILE: □, OTHER □ (explain) N/A Cubic yards: I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \(\times \), a general permit \(\times \), or an alternative OCD-approved plan \(\times \). 05/17/06 Date: Jeff Blagg – P.E. # 11607 Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	4 - Pt @ 9'	Date Reported:	05-15-06
Laboratory Number:	37102	Date Sampled:	05-10-06
Chain of Custody No:	15960	Date Received:	05-10-06
Sample Matrix:	Soil	Date Extracted:	05-12-06
Preservative:	Cool	Date Analyzed:	05-12-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	0.2	0.2
Diesel Range (C10 - C28)	0.4	0.1
Total Petroleum Hydrocarbons	0.6	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Elliott GC Y 1 Sep Pit.

Analyst mhalten

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	4 - Pt @ 9'	Date Reported:	05-15-06
Laboratory Number:	37102	Date Sampled:	05-10-06
Chain of Custody:	15960	Date Received:	05-10-06
Sample Matrix:	Soil	Date Analyzed:	05-12-06
Preservative:	Cool	Date Extracted:	05-12-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
_			
Benzene	ND	1.8	
Toluene	65.7	1.7	
Ethylbenzene	22.4	1.5	
p,m-Xylene	75.0	2.2	
o-Xylene	22.8	1.0	
Total BTEX	186		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
•	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Elliott GC Y 1 Sep Pit.

/ Mutu m Walter

Review



Chloride

Client: Blagg / BP Sample ID: 4 - Pt @ 9' Lab ID#: 37102 Sample Matrix: Soil Preservative: Cool Condition:

Project #: 94034-010 Date Reported: 05-12-06 Date Sampled: 05-10-06 Date Received: 05-10-06 Date Analyzed: 05-12-06 Chain of Custody: 15960

Parameter

Concentration (mg/Kg)

Total Chloride

74.0

Reference:

Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Elliott GC Y 1 Sep Pit.

Cool and Intact

Cul Well

Mustur Mualdes Review



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	C @ 9'	Date Reported:	05-15-06
Laboratory Number:	37101	Date Sampled:	05-10-06
Chain of Custody No:	15960	Date Received:	05-10-06
Sample Matrix:	Soil	Date Extracted:	05-12-06
Preservative:	Cool	Date Analyzed:	05-12-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	0.2	0.2
Diesel Range (C10 - C28)	0.5	0.1
Total Petroleum Hydrocarbons	0.7	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Elliott GC Y 1 Sep Pit.

(Mother Walles Analyst

Review

Reul Wull



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	C @ 9'	Date Reported:	05-15-06
Laboratory Number:	37101	Date Sampled:	05-10-06
Chain of Custody:	15960	Date Received:	05-10-06
Sample Matrix:	Soil	Date Analyzed:	05-12-06
Preservative:	Cool	Date Extracted:	05-12-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

	Concentration	Det. Limit	
Parameter	(ug/Kg)	(ug/Kg)	
Benzene	59.7	1.8	
Toluene	23.1	1.7	
Ethylbenzene	10.6	1.5	
p,m-Xylene	53.4	2.2	
o-Xylene	24.7	1.0	
Total BTEX	172		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Elliott GC Y 1 Sep Pit.

Analyst MI Daltes

Pul Wall
Review



Chloride

Client: Blagg / BP Project #: 94034-010 Sample ID: C @ 9' Date Reported: 05-12-06 Lab ID#: 37101 Date Sampled: 05-10-06 Sample Matrix: Soil Date Received: 05-10-06 Preservative: Cool Date Analyzed: 05-12-06 Condition: Cool and Intact Chain of Custody: 15960

Parameter Concentration (mg/Kg)

Total Chloride 66.0

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Elliott GC Y 1 Sep Pit.

Ruh Stull
Review

Austra Milater

CHAIN OF CUSTODY RECORD

Client / Project Name			Project Location					AN	ALYSIS / PA	ARAMETE	RS			
BLAGG/BP	<u> </u>		ELLIOTT (ic Y 1										
Sampler:	а		Client No.			တ္					F	lemarks		
2-0-3	GS4,		94032	(-010	No. of	alue	k. 1	1,						
Sample No./ Identification	Sample Date	Sample Time	Lab Number	Sample Matrix	Z	Containers	BIEX	3						
C @ 9'	5/10/06	1155	37101	SOIL	-	×	×	$ \times $			SEP	RT	.,	
C @ Q' 4-Pt @ Q'		1205	37102	11	(上	上	><			11			
					!									
												,,, ., ., .		
Relinquished by: (Signai	iure)		يتو	Date Time	Received b	y÷)(Signat	űle)	1. Ü				Date //		me
Relinguished by: (Signal	ure)			10/06 1426	Received b			all				10/06	, 14	26
Relinquished by: (Signai	ure)				Received b	y: (Signati	ure)							
			,	ENVIRO	TECL	In	C,				Sample	Receipt	1	
			į									Υ	N	N/A
				5796 U. Farmington,	S. Highway New Mexid		1			Rec	eived Intact		/	
) 632-0615					Cool	- Ice/Blue Ice			



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC		Project #:		N/A
Sample ID:	05-12-06 QA/Q	(C	Date Reported:		05-15-06
Laboratory Number:	37101		Date Sampled:	-	N/A
Sample Matrix:	Methylene Chlori	de	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		05-12-06
Condition:	N/A		Analysis Request	ed:	TPH
Gasoline Range C5 - C10	l-Cal Date 02-04-05	I-Cal RF:	*C-Cal RF: 1.4779E+003	% Difference 0.10%	Accept Range
Diesel Range C10 - C28	02-04-05	1.7340E+003	1.7374E+003	0.20%	0 - 15%
Blank Conc. (mg/L - mg/K Gasoline Range C5 - C10	and the same of th	Concentration ND		Detection Lin	HEŞ "
Diesel Range C10 - C28		ND		0.1	
Total Petroleum Hydrocarbons	i	ND		0.2	
. otal . oti oloainiyai ooai boile					
Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Range) .*
	Sample 0.2	Duplicate 0.2	% Difference	Accept. Range 0 - 30%	9 ,*
Duplicate Conc. (mg/Kg)	"But relied to 1 to 8 Butter of Miller	Very trible of Marie and	a a root a resultant comment.	Caramar	9 , 9
Duplicate Conc. (mg/Kg)** Gasoline Range C5 - C10	0.2	0.2 0.5	0.0% 0.0%	0 - 30%	() (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
Duplicate Conc. (mg/Kg) Gasoline Range C5 - C10 Diesel Range C10 - C28	0.2 0.5	0.2 0.5	0.0%	0 - 30% 0 - 30%	Accept Range 75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 37101 - 37102, 37108 - 37113.

Analyst

Sleul Yeul



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	F	Project #:		N/A
Sample ID:	05-12-BTEX QA/C	QC [Date Reported:		05-15-06
Laboratory Number:	37101	I	Date Sampled:		N/A
Sample Matrix:	Soil	ſ	Date Received:		N/A
Preservative:	N/A	ĺ	Date Analyzed:		05-12-06
Condition:	N/A	,	Analysis:		BTEX
Calibration and Detection Limits (ug/L)	I-Cal RE	C-Cal RF: Accept. Rang	%Diff.	Blank Conc	Detect. Limit
Benzene	6.6467E+007	6.6601E+007	0.2%	ND	0.2
Toluene	7.6089E+007	7.6241E+007	0.2%	ND	0.2
Ethylbenzene	4.4943E+007	4.5033E+007	0.2%	ND	0.2
p,m-Xylene	1.4564E+008	1.4593E+008	0.2%	ND	0.2
o-Xylene	7.0689E+007	7 0831E+007	0.2%	ND	0.1
Duplicate Conc. (ug/Kg) Benzene	Sample 59.7	and the second s	., 8° , 5°6, 5000 , 2000 5° 400 20 200	Accept Range	Detect Limit
Benzene Toluene Ethylbenzene p,m-Xylene	59.7 23.1 10.6 53.4	59.7 23.1 10.5 52.4	0.0% 0.0% 0.9% 1.9%	0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2
Benzene Toluene Ethylbenzene	59.7 23.1 10.6	59.7 23.1 10.5 52.4 24.5	0.0% 0.0% 0.9%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	59.7 23.1 10.6 53.4 24.7	59.7 23.1 10.5 52.4 24.5	0.0% 0.0% 0.9% 1.9% 0.8%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc (ug/Kg)	59.7 23.1 10.6 53.4 24.7	59.7 23.1 10.5 52.4 24.5 Amount Spiked	0.0% 0.0% 0.9% 1.9% 0.8%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (úg/Kg) Benzene Toluene	59.7 23.1 10.6 53.4 24.7 Sample	59.7 23.1 10.5 52.4 24.5 Amount Spiked 50.0 50.0	0.0% 0.0% 0.9% 1.9% 0.8%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (úg/Kg) Benzene Toluene Ethylbenzene	59.7 23.1 10.6 53.4 24.7 Sample 59.7 23.1 10.6	59.7 23.1 10.5 52.4 24.5 Amount Spiked 50.0 50.0 50.0	0.0% 0.0% 0.9% 1.9% 0.8% Spiked Sample	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.9% 100.0% 99.8%	1.8 1.7 1.5 2.2 1.0 Accept Range 39 - 150 46 - 148 32 - 160
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg)	59.7 23.1 10.6 53.4 24.7 Sample 59.7 23.1	59.7 23.1 10.5 52.4 24.5 Amount Spiked 50.0 50.0 50.0 100	0.0% 0.0% 0.9% 1.9% 0.8% Spiked Sample	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.9% 100.0%	1.8 1.7 1.5 2.2 1.0 Accept Range 39 - 150 46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for Samples 37101 - 37102, 37107, 37110 - 37113.

Revie