District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No 🗌 Type of action: Registration of a pit or below-grade tank \(\bigcirc Closure of a pit or below-grade tank \(\bigcirc Telephone: (505)-326-9200 e-mail address: Operator: BP AMERICA PROD. CO. Address: 200 ENERGY COURT, FARMINGTON, NM 87410 API#: 30-045- 23278 U/L or Qtr/Qtr_B Sec 24 T 31N R 10W Facility or well name: ATLANTIC LS #15 County: SAN JUAN Latitude 36.88883 Longitude 107.83215 NAD: 1927 🗌 1983 🛛 Surface Owner Federal 🖾 State 🔲 Private 🔲 Indian 🔲 RCVD APR5'07 Pit Below-grade tank MIL CONS. DIV. Type: Drilling ☐ Production ☐ Disposal ☒ _SEPARATOR Volume: ____ bbl-Type-&fluid: DIST. 3 Workover ☐ Emergency ☐ Construction material Double-walled, with leak detection? Yes I If net, explain why not. Lined Unlined Liner type: Synthetic Thickness _____mil Clay ___ Pit Volume Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 0 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more (0 points) (20 points) Wellhead protection area: (Less than 200 feet from a private domestic 0 No (0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) 0 irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more (0 points) 0 **Ranking Score (Total Points)** If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite \(\square\) offsite \(\square\) If offsite, name of facility __. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No 🛛 Yes 🔲 If yes, show depth below ground surface ______ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments PIT LOCATED APPROXIMATELY FT. N9E 27 FROM WELL HEAD. PIT EXCAVATION: WIDTH N/Aft., LENGTH N/Aft., DEPTH N/Aft. PIT REMEDIATION: CLOSE AS IS: ☑, LANDFARM: ☐, COMPOST: ☐, STOCKPILE: ☐, OTHER ☐ (explain) Cubic vards: | N/A BEDROCK BOTTOM I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ⊠, a general permit □, or an alternative OCD-approved plan ⊠. 02/08/06 Date **Jeff Blagg – P.E. # 11607** Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. Date: AUU U 9 2007 Deputy Oil & Gas Inspection Approval: Printed Name/Title

10' PD
A () IO A
weic
PD = PIT DEPRESSION, B.G. = BELOW GRADE; B = BELOW

CALLOUT:

r	くにと	ADING					
SAMPLI ID	E	FIELD HEA (ppn					
@							
@							
@							1
@				A	Mary mary market	-10	
@					_		
@ @ ;- <i>Po</i> ~	7	331	1				
0 m	مزد ور				7		
0 25				0'			ļ
				1			j
				الما			
	ВS	AMPLES	3	,	/ ,	, r = ""	
AMPLE ID	Α	NALYSIS	TIME		. John	BEDIL	2
المامان أرس	77	Spet .	1045		/ 4	SEUK	
	127	<i>¥</i> 5:		1	*		
	-	i]			
	_						
	104	955ED)					

TRAVEL NOTES:



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	5 - Point @ 8'	Date Reported:	02-08-06
Laboratory Number:	36153	Date Sampled:	02-03-06
Chain of Custody No:	15512	Date Received:	02-07-06
Sample Matrix:	Soil	Date Extracted:	02-07-06
Preservative:	Cool	Date Analyzed:	02-08-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Atlantic LS 15 Sep Pit.

Analyst

(Mistre of Walters Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	5 - Point @ 8'	Date Reported:	02-08-06
Laboratory Number:	36153	Date Sampled:	02-03-06
Chain of Custody:	15512	Date Received:	02-07-06
Sample Matrix:	Soil	Date Analyzed:	02-08-06
Preservative:	Cool	Date Extracted:	02-07-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	1.8	
Toluene	19.4	1.7	
Ethylbenzene	68.1	1.5	
p,m-Xylene	56.5	2.2	
o-Xylene	3.9	1.0	
Total BTFX	148	•	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Atlantic LS 15 Sep Pit.

Analyst

Review



Chloride

Blagg / BP Client: Project #: 94034-010 Sample ID: 5-Point @ 8' Date Reported: 02-08-06 Lab ID#: 36153 Date Sampled: 02-03-06 Sample Matrix: Soil Date Received: 02-07-06 Preservative: Cool Date Analyzed: 02-08-06 Condition: Cool and Intact Chain of Custody: 15512

Parameter Concentration (mg/Kg)

Total Chloride 0.8

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Atlantic LS 15 Sep Pit.

Analyst

Review

CHAIN OF CUSTODY RECORD

Client / Project Name			Project Location													
BLACE/B		10	ATLANT	ic LS	15					ANA	LYSIS / PAI	RAMETERS				
Sampler	4		Client No.				S						Re	marks		
9-0-	Ls5		94034	1-01	0		No. of Containers	7	N. W.	6)	Í					
Sample No./	Sample	Sample	Lab Number		Sample		Sont.	1 p	BIEX 802	3						
Identification	Date	Time	Lab Number		Matrix			V .	70							
5- POINT @8	2/3/06	1045	36153	5	201L		1	×	X	メ		5	EP	PT	-	
											-					
				_												
				_												
				-												
						•	!									
Relinquished by: (Signatur	re)		<u></u>	Date	Time	Recei	ved bv:	(Signatu	ıre)		i			ate	Ti	me
196-30			2,	17/06	1455		Mid	·	~ 1	1)001	+10		2/-	7/06	14	155
Relinquished by: (Signatur	re)/			/		Recei	ved by:	(Signatu	ire)	Dall	·		- A	1100		90
V																
Relinquished by: (Signatur	re)					Recei	ved by:	(Signatu	ıre)			•				
														<i></i>		
				ENV	IRO °	TE(JH		S.				Sample R	eceipt		
				The Cart	en es app		7.00	Sec. 10	S (8)					Y	Ν	N/A
					796 U.S				4			Received	Intact			
				rarm	ington, N (505)			8/40	1			Cool - Ice/	Blue Ice	/		
					` /						_	_ i		1 1		



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

-					
Client:	QA/QC	~	Project #:		N/A
Sample ID:	02-08-06 QA/	QC	Date Reported:		02-08-06
Laboratory Number:	36150		Date Sampled:		N/A
Sample Matrix:	Methylene Chlo	ride	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		02-08-06
Condition:	N/A		Analysis Reques	sted:	TPH
	I-Cal Date	I-Cal RF:	C-Cal RF	% Difference	Accept Range
Gasoline Range C5 - C10	02-04-05	9.9237E+002	9.9337E+002	0.10%	0 - 15%
Diesel Range C10 - C28	02-04-05	1.0044E+003	1.0064E+003	0.20%	0 - 15%
Blank Conc. (mg/L - mg/Kg Gasoline Range C5 - C10	United States Control of the Control	ND		0.2	
Diesel Range C10 - C28		ND		0.1	
Total Petroleum Hydrocarbons		ND		0.2	
Duplicate Conc. (mg/Kg) Gasoline Range C5 - C10	Sample ND	Duplicate ND	% Difference 0.0%	Accept. Range 0 - 30%	A.
Diesel Range C10 - C28	32.9	33.2	0.9%	0 - 30%	
Spike Conc. (mg/Kg)	Sample C	Spike Added	Spike Result	 Recovery	Accept Range
Gasoline Range C5 - C10	ND	250	250	100.0%	75 - 125%
Diesel Range C10 - C28	32.9	250	282	99.8%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 36150 - 36151, 36153 - 36154, 36156 - 36161.

Analyst



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	P	roject #:		N/A
Sample ID:	02-08-BTEX QA/0		ate Reported:		02-08-06
Laboratory Number:	36150		ate Sampled:		N/A
Sample Matrix:	Soil		ate Received:		N/A
Preservative:	N/A		ate Analyzed:		02-08-06
Condition:	N/A		nalysis:		BTEX
Calibration and	ી-Cal RF: ૣે	C-Cal RF	%Diff.	Blank	Detect
Detection Limits (ug/L)		Accept. Range	e 0 - 15%	Conc	Limit
Benzene	1.3635E+007	1 3663E+007	0.2%	ND	0.2
Toluene	2.3246E+007	2.3293E+007	0.2%	ND	0.2
Ethylbenzene	1.9107E+007	1.9146E+007	0.2%	ND	0.2
p,m-Xylene	4.1729E+007	4 1812E+007	0.2%	ND	0.2
	1.9115E+007	1.9153E+007	0.2%	ND	0.1
o-Xylene Duplicate Conc. (ug/Kg) Benzene		ÜÜüplicate		Accept Range	Detect: Limit
Duplicate Conc. (ug/Kg)	Sample	ND 9.1 4.2 ND	%Diff.	a i i i i i i i i i i i i i i i i i i i	the province of the transfer of the
Duplicate Conc. (ug/Kg) Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg) Benzene Toluene	Sample ND 9.2 4.3 ND ND Sample ND 9.2	ND 9.1 4.2 ND ND Spiked 50.0 50.0	%Diff. 0.0% 1.1% 2.3% 0.0% 0.0% Spiked Sample 49.9 59.1	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.8% 99.8%	1.8 1.7 1.5 2.2 1.0 Accept Range
Duplicate Conc. (ug/Kg) Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg) Benzene Toluene Ethylbenzene	Sample ND 9.2 4.3 ND ND Sample ND 9.2 4.3	Duplicate ND 9.1 4.2 ND ND Amount Spiked 50.0 50.0 50.0	%Diff. 0.0% 1.1% 2.3% 0.0% 0.0% Spiked Sample.	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	1.8 1.7 1.5 2.2 1.0
Duplicate Conc. (ug/Kg) Benzene Toluene Ethylbenzene p,m-Xylene	Sample ND 9.2 4.3 ND ND Sample ND 9.2	Duplicate ND 9.1 4.2 ND ND Amount Spiked 50.0 50.0 50.0	%Diff. 0.0% 1.1% 2.3% 0.0% 0.0% Spiked Sample 49.9 59.1	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 99.8% 99.8%	1.8 1.7 1.5 2.2 1.0 Accept Range

ND - Parameter not detected at the stated detection limit.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 36150 - 36151, 36153 - 36154, 36156 - 36159.

Analyst