

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2007 AUG 13 AM 7 54

1. Type of Well
GAS

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit J (NWSE), 1785' FSL & 1580' FEL, Section 32, T27N R4W, NMPM

5. Lease Number
SF-0806706. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
San Juan 27-4 Unit #54G

9. API Well No.

30-039-30234

10. Field and Pool

Basin Dakota

Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection

RCVD AUG 14 '07
OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

7/28/07 MIRU Aztec 301. NU BOP. PT casing to 600# 30/min - good test. RIH w/8-3/4" bit. D/O cement to 4062' intermediate. RIH w/93 jts 20# & 2 jts 23# 7" J-55 casing set @ 4051'. RU to cement. 8/1/07 Lead- pumped 600 sx(1278cf-227bbls) Premium Lite FM Cement w/.4% SMS, 3% CaCl₂, .4% FL-52A, .25 #/sx Cello-Flake, 5% LCM-1. Tail- pumped 95 sx(131cf-23bbls) Type 111 Cement w/1% CaCl₂, .2% FL-52A, .25 #/sx Cello-Flake. Dropped plug & displaced w/158 bbls FW. Bumped plug to 1660#. Plug Down @ 23:41. Circ 110 bbls cement to pit. RD cement.

8/2/07 PT casing to 1500# 30/min -good test. RIH w/6-1/4" bit. D/O cement to 8256' (TD). TD reached on 8/8/07. Circ hole. RIH w/158 jts 10.5# & 30 jts 11.6# J-55 ST & C, 10 jts 4 1/2" 11.6# J-55, 1 jts 4 1/2" 11.6# N-80 casing set @ 8250'. RU to cement. 8/9/07 Pumped pre-flush of 10 bbls H₂O/10 bbls MCII/10 bbls H₂O. Pumped Scavenger 9 sx(28cf5bbls) Premium Lite HS FM Cement w/.3% CD-32, 1% FL-52A, .25 #/sx Cello-Flake, & 6.25 #/sx LCM-1. Tail-pumped 297 sx(588cf-105bbls) Premium Lite HS FM Cement w/.3% CD-32, 1% FL-52A, .25 #/sx Cello-Flakes, & 6.25 #/sx LCM-1. Dropped plug & displaced w/131 bbls H₂O. Bumped Plug to 1800#. Plug down @ 17:0 hrs. RD cement. ND BOP. RD. RR.

14. I hereby certify that the foregoing is true and correct.

Report to c 4 1/2 next report

Signed

Tracey N. Monroe

Tracey N. Monroe

Title Regulatory Technician

Date 8/10/07

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Date

ACCEPTED FOR RECORD

AUG 13 2007

NMOC

FARMINGTON FIELD OFFICE