## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED	
OM B No 1004-0137	
Expires: March 31, 200	7

Lease Senal No

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals.	SF 078988  16 11 Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE- Other instructions on reverse side.  1 Type of Well	7. If Unit or CA/Agreement, Name and/or No.
2 Name of Operator Devon Energy Production Company, L.P.	8 Well Name and No. NEBU 248 9 API Well No
3a Address 20 N. Broadway, Oklahoma City, OK 73102  3b Phone No (include area code) 405-552-7917  4 Location of Well (Footage, Sec., T., R., M., or Survey Description)	30-045-34148  10 Field and Pool, or Exploratory Area Rosa Pictured Cliffs
SL - 720' FNL & 60' FWL, NW NW, Unit D, Sec. 20, T31N, R6W BHL - 1,150' FNL & 750' FWL, NW NW, Unit D, Sec. 20, T31N, R6W	11. County or Parish, State San Juan, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, RI	EPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Acidize	Well Integrity  ✓ Other Spud Notice &
13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of an If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and tru Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA Require following completion of the involved operations. If the operation results in a multiple completion or recompletion in testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclams determined that the site is ready for final inspection.)	e vertical depths of all pertinent markers and zones.  It subsequent reports shall be filed within 30 days  In a new interval, a Form 3160-4 shall be filed once
The above referenced well was spud on 8/13/07 at 13:15 hours.	
Drilled 12 1/4" hole to 290' on 8/15/07, set 7 jts of 9 5/8", H-40, ST&C, 32.3# casing at 281'. Cemen CaCl2 and 1/4# PSX Celloflake. Circulated 17 bbls of cement to surface. Casing test will be on nex	

DIST. 3

ACCEPTED FOR RECORD

FARMINGTON FIELD OFFICE

	S. If salker?
tle Senior Staff Operations Technician	
ate August 20	D, 2007
Title	Date
Office	
);	DR STATE OFFICE USE

(Instructions on page 2)