

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2007 AUG 28 PM 1: 57

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON**

RESOURCES OIL &amp; GAS COMPANY LP

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit C (NENW), 1180' FNL &amp; 1975' FWL, Sec. 13, T30N, R9W, NMPM

5. Lease Number  
SF-0772316. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name &amp; Number

Shaw #1M

9. API Well No.

30-045-34255

10. Field and Pool

Basin DK / Blanco MV

11. County and State  
San Juan Co., NM**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

## Type of Submission

## Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - casing☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to InjectionRCVD SEP 6 '07  
OIL CONS. DIV.

DIST. 3

**13. Describe Proposed or Completed Operations**

8/15/07 RIH w/8-3/4" bit & tagged cement @ 185'. D/O cement and then formation to 2863'. Circ. Hole. RIH w/69 jts 7", 20#, J-55 casing and set @ 2848'. RU to cement. Pumped 20 bbls mud clean ahead of 350 sx (748 cf - 133 bbls) Premium Lite FM cement w/3% CaCl, 8% Bentonite, .25#/sx Celloflake, .4% FL-52A, 5#/sx LCM-1, & .4% SMS. Tailed w/61 sx (84 cf - 15 bbls) Type III cement w/1% CaCl, .25#/sx Celloflake, .2% FL-52A. Dropped plug and displaced w/114 bbls FW. Circ. 43 bbls cement to surface. Plug down @ 0200 hrs 8/16/07. RD BJ. 8/17/07 PT casing to 250 #/3min & 1800#/30 min. Good test.

11.6 # 8/17/07 RIH w/6-1/4" bit & tagged cement @ 2790'. D/O cement and then formation to 7143' (TD). TD reached 8/18/07. Circ. Hole. RIH w/ 166 jts 4-1/2" L-80 LT&C casing and set @ 7138'. RU BJ services. Pumped preflush of 10 bbls gel & 2 bbls water. Pumped 326 sx (647 cf - 115 bbls) Premium Lite High Strength FM cement w/ .3% CD-32, .25#/sx Celloflake, 1% FL-52A, 6.25#/sx LCM-1. Dropped plug and displaced w/110 bbls water. Bumped plug @ 2010 hrs 8/19/07 w/1953 #. RD BJ. Land mandrell in WH. RD & released rig @ 0200 hrs 8/20/07. Will report casing PT & TOC on next report. Tests will be conducted by completion rig.

**14. I hereby certify that the foregoing is true and correct.**Signed Patsy Clugston Title Regulatory Specialist Date 8/27/07

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOC

ACCEPTED FOR RECORD

SEP 04 2007

FARMINGTON FIELD OFFICE  
BY T. Salyers