

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO 1004-0137

Expires December 31, 1991

5 LEASE DESIGNATION AND SERIAL NO

NM - 011350-A

6 INDIAN, ALLOTTEE OR TRIBE NAME

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a TYPE OF WELL OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐

SEP 05 2007
Bureau of Land Management
Farmington Field Office

UNIT AGREEMENT NAME

San Juan 29-5 Unit NMNM-78415A-A

8 FARM OR LEASE NAME, WELL NO

San Juan 29-5 Unit #35M

9 API WELL NO.

30-039-30155-0002

10 FIELD AND POOL, OR WILDCAT

Basin DK/Blanco MV

11 SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 34 T29N R5W, NMPM

2 NAME OF OPERATOR

ConocoPhillips

3 ADDRESS AND TELEPHONE NO

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Unit D (NWNW) 610' FNL, 755' FWL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO DATE ISSUED

12 COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

15. DATE SPUNDED

6/12/07

16. DATE T.D. REACHED

6/24/07

17. DATE COMPL. (Ready to prod.)

8/31/07

18 ELEVATIONS (DF, RKB, RT, BR, ETC)*

GL 6792' KB 6808'

19. ELEV CASINGHEAD

20 TOTAL DEPTH, MD & TVD

8197' 8209'

21 PLUG, BACK T.D., MD & TVD

8192'

22. IF MULTIPLE COMPL., HOW MANY*

2

23. INTERVALS DRILLED BY

ROTARY TOOLS

yes

CABLE TOOLS

24 PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesa Verde 5366' - 6266'

25 WAS DIRECTIONAL SURVEY MADE

No

26 TYPE ELECTRIC AND OTHER LOGS RUN

Cement bond Log w/Gamma Ray Casing Collars / Temp Survey

27 WAS WELL CORED

No

28 CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	232'	12 1/4"	surface; 75sx (121 cf)	5 bbls
7" J-55	20#, 23#	4068'	8 3/4"	surface; 597sx (1204 cf)	TOC = 815'
4 1/2" J-55	11.6#, 10.5#	8209'	6 1/4"	TOC 2300'; 313sx (620 cf)	

29 LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	7971'	

31 PERFORATION RECORD (Interval, size and number)

@1SPF
LMF 5730' - 5916'
PLO 5950' - 6266'
CH 5366' - 5636'
UMF 5648' - 5690'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC

5730' - 6266' 60Q Slickfoam w/99600# 20/40 Brady Sand. Total N2 = 1283600 SCF.
5366' - 5690' 60Q Slickfoam, w/100760# 20/40 Brady Sand. Total N2= 1278000 SCF.

RCUD SEP 10 '07
OIL CONS. DIV.
DIST. 8

33 PRODUCTION

DATE FIRST PRODUCTION SI W/O Facilities PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing WELL STATUS (Producing or shut-in) SI

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO
8/28/07	1	1/2"			54.46 mcf	.04 bw	
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR)	
1042#	587#			1307 mcf/d	1 bwpd		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35 LIST OF ATTACHMENTS

This is a MV/DK well being DHC per order #2565AZ

36 I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED J. M. M... TITLE Regulatory Technician

DATE 9/4/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

SEP 07 2007

FARMINGTON FIELD OFFICE
BY TL Salyers

Ojo Alamo	2955'	3116'
Kirtland	3116'	3395'
Fruitland	3395'	3769'
Pictured Cliffs	3769'	3984'
Lewis	3984'	4408'
Huerfanito Bentonite	4408'	4749'
Chacra	4749'	5362'
Mesa Verde	5362'	5638'
Menefee	5638'	5946'
Point Lookout	5946'	6274'
Mancos	6274'	7218'
Gallup	7218'	7916'
Greenhorn	7916'	7973'
Graneros	7973'	8044'
Dakota	8044'	

White, cr-gr ss.
 Gry sh interbedded w/tight, gry, fine-gr ss.
 Dk gry-gry carb sh, coal, grn silts, light-
 med gry, tight, fine gr ss.
 Bn-Gry, fine grn, tight ss.
 Shale w/siltstone stringers
 White, waxy chalky bentonite
 Gry fn grn silty, glauconitic sd stone
 w/drk gry shale
 Light gry, med-fine gr ss, carb sh
 & coal
 Med-dark gry, fine gr ss, carb sh & coal
 Med-light gry, very fine gr ss w/frequent
 sh breaks in lower part of formation
 Dark gry carb sh.
 Lt gry to brn calc carb micac glauc
 silts & very fine gr gry ss w/irreg.interbed sh
 Highly calc gry sh w/thin lmst.
 Dk gry shale, fossil & carb w/pyrite incl.
 Lt to dk gry foss carb sl calc sl silty
 ss w/pyrite incl thin sh bands clay & shale breaks

Ojo Alamo	2955'
Kirtland	3116'
Fruitland	3395'
Pic.Cliffs	3769'
Lewis	3984'
Huerfanito Bent.	4408'
Chacra	4749'
Mesa Verde	5362'
Menefee	5638'
Point Lookout	5946'
Mancos	6274'
Gallup	7218'
Greenhorn	7916'
Graneros	7973'
Dakota	8044'

W-ARIZONA

6000

100 - 212

100 - 212