· 260-30-045-27135 3 - 30-045-09276

٠, ٠,

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO 30-045-2049/

Operator MERIDIAN OIL CO.	Location: Unit N Sec. 34 Twp 30 Rng 9
Name of Well/Wells or Pipeline Serv	viced RIDDLE A COM # 260, # 3, # 9
	cps 54w
Elevation 5716 Completion Date 8/20/	90 Total Depth 65 Land Type N/A
Casing Strings, Sizes, Types & Dep	ths 47ft. 8" PVC Casing
If Casing Strings are cemented, she	ow amounts & types used N/A
If Cement or Bentonite Plugs have I	been placed, show depths & amounts used
Depths & thickness of water zones	with description of water: Fresh, Clear
Salty, Sulphur, Etc. 30 ft. to 40 ft	•
Depths gas encountered: N/A	
Ground bed depth with type & amount	t of coke breeze used:
65 ft. with 500 lbs Ashbury Petroleum	Coke
Depths anodes placed: 60ft., 53 ft.	
Depths vent pipes placed: 65 ft.	HE E VE LO E M
Vent pipe perforations: 20'	MAY 3 1 1991
Remarks: gb #3 Well #2	OIL CON. DIV
	\ DIST. 3

If any of the above data is unavailable, please indicate so. Copies of al logs, including Drillers Log, Water Analyses & Well Bore Schematics shoul be submitted when available. Unplugged abandoned wells are to be include

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

· 260- 30-065-27135

3 - 30-045-09276

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS. 9-30-045-20491

:::

Operator MERIDIAN OIL CO.	Location: Unit N_Sec. 34_Twp 30 Rng o
Name of Well/Wells or Pipeline Serv	ced RIDDLE A COM # 260, # 3, # 9
4-7-1015	cps 54w
Elevation 5716 Completion Date 8/20/90	Total Depth 102 Land Type N/A
Casing Strings, Sizes, Types & Deptl	50 ft. 8" PVC Casing
If Casing Strings are cemented, show	amounts & types used N/A
If Cement or Bentonite Plugs have be	en placed, show depths & amounts use:
Depths & thickness of water zones w	ith description of water: Fresh, Clea
Salty, Sulphur, Etc. 30 to 40 ft. 102	
Depths gas encountered: 102 f	t.
Ground bed depth with type & amount	of coke breeze used: NA 500 lbs
·	
Depths anodes placed: 60', 53'	REGEIVED
Depths vent pipes placed: N/A	MAY31 1991
Vent pipe perforations: N/A	OIL CON. DIV
Remarks: Well # 1 Abandoned- cemented gb #3	/ redrilled/ cemented - drilled with mud

If any of the above data is unavailable, please indicate so. Copies of a logs, including Drillers Log, Water Analyses & Well Bore Schematics show be submitted when available. Unplugged abandoned wells are to be includ-

Land Type may be shown: F-Federal; I-Indian; S-State; P-Pee. If Federal or Indian, add Lease Number.

· · · 260 - 30-045-27/35 3 30-045-09276

#3

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO 30-045- 20491

Operator_	MERIDIAN OIL C	0.	I	Locatio	on: l	Jnit <u>N</u>	_Sec. <u>34</u>	_Twp_30	_Rng
Name of W	ell/Wells or	Pipeline	Service	d RII	DDLE A	A COM #	260, #3	, #9	
	· · · · · · · · · · · · · · · · · · ·				 			cps 5	4w
Elevation	5716 Complet	on Date 8	/20/90	Total	Dept	.h _{_65ft}	Land	Type_	N/A
Casing St	rings, Sizes,	Types &	Depths	47 ft.	8" P	VC Casi	ng		
If Casing	Strings are	cemented	, show a	mount	B & 1	types	used	N/A	
If Cement	or Bentonite	Plugs ha	ive beer	place	ed, 8	how d	epths &	amoun	ts use
Depths &	thickness of	water zor	nes with	desci	ripti	ion of	water:	Fresh	, Clea
Salty, Su	lphur, Etc	30 to 4	0 ft.	· · · · · · · · · · · · · · · · · · ·					
Depths ga	s encountered	l:		N/A					
Ground be	d depth with	type & am	ount of	coke	bree	eze us	ed:		
65 ft. w	ith 500 lbs Ash	bury Petrol	eum Coke				····		
Depths and	odes placed:	53 ft. 45	ft.		2000	400			
Depths ve	nt pipes plac	ed: 65 f	t.		R	E G	EIVI		
Vent pipe	perforations	20	1			MAY3	1 1991	<u>U</u>	
	ab				Ó		N. DIV	,	
_						\ DIS	T. 3		

If any of the above data is unavailable, please indicate so. Copies of a logs, including Drillers Log, Water Analyses & Well Bore Schematics shows be submitted when available. Unplugged abandoned wells are to be include

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

1.4 (1.4)

· 260 - 30 - 045 - 27135 3 30 - 045 - 09276

DATA SHEET FOR DEEP GROUND BED. CATHODIC PROTECTION: WELLS... NORTHWESTERN. NEW: MEXICO 20191

Operator MERIDIAN OIL CO.	Location: Unit N Sec. 34 Twp 30 Rng 9
Name of Well/Wells or Pipeline Ser	viced RIDDLE A COM # 260, #3, #9
	cns 54w
Blevation 5716 Completion Date 8/20/	90 Total Depth 65 ft. Land Type N/A
Casing Strings, Sizes, Types & Dep	the 47 ft. 8" PVC Casing
If Casing Strings are cemented, she	ow amounts & types used N/A
If Cement or Bentonite Plugs have	been placed, show depths & amounts use
Depths & thickness of water zones	with description of water: Fresh, Clea
Salty, Sulphur, Etc. 30 to 40 ft.	
Depths gas encountered:	N/A
Ground bed depth with type & amount	t of coke breeze used:
65 ft. with 500 lbs Ashbury Petroleum	Coke
Depths anodes placed: 58ft, 50 ft.	
Depths vent pipes placed: 65 ft.	DECEIVED
Vent pipe perforations: 20'	MAY3 1 1001
Remarks: qb #3 Well #4	OIL CON DIV
	DIST. 3

If any of the above data is unavailable, please indicate so. Copies of allogs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be include

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

260 30-045-27/35 3 30-045-09276

:::

DATA SHEET FOR DEEP GROUND BED. CATHODIC PROTECTION. WELLS... 9 - 30-045-70491

vation 5716 Completion Date 8/20/90 Totaing Strings, Sizes, Types & Depths 87 Casing Strings are cemented, show amount or Bentonite Plugs have been plugs. N/A ths & thickness of water sones with decay, Sulphur, Etc. 30 to 40 ft.	ft. 8" PVC	Casing	Cps 54w Type N/A N/A
Casing Strings are cemented, show amounted or Bentonite Plugs have been plugs. N/A ths & thickness of water sones with de	ft. 8" PVC	Casing	Type N/A N/A
Casing Strings are cemented, show amounted or Bentonite Plugs have been plugs. N/A ths & thickness of water sones with de	ft. 8" PVC	Casing	N/A
Casing Strings are cemented, show amounted the strings are cemented, show amounted the strings have been plotted in the strings are cemented, show amounted the strings are cemented, show amounted in the strings are cemented, show amounted the strings are cemented, show amounted in the strings are cemented in the	nts & type	es used	
Cement or Bentonite Plugs have been pl N/A		÷	
Cement or Bentonite Plugs have been pl N/A		÷	
Cement or Bentonite Plugs have been pl N/A		÷	
N/A ths & thickness of water sones with de	aced, show	depths 6	amounts use
N/A ths & thickness of water sones with de	aced, show	e deptus e	amounts use
ths & thickness of water zones with de			
v. Sulphur Rto 30 to 40 ft	scription	of water	Presh, Clea
Mi parhari acci 20 co 40 cc.			
chs gas encountered: N/A			,
and bed depth with type & amount of co	ke breeze	used:	
	NO DAGGE	4644.	
ft. 500 lbs Ashbury Petroleum Coke	Sand Control	- A	
hs anodes placed: 55 ft. & 48 ft.		III MAY:	T 1991.
chs vent pipes placed: 65 ft.			N. DIV.
pipe perforations: 20'			ST. 3
	T 65' 10ST 1	ANODE	
xks: ab #3 Well #5 Well #6 CAVED A	UU LUST .	ANUUE.	

If any of the above data is unavailable, please indicate so. Copies of a logs, including Drillers Log, Water Analyses & Well Bore Schematics shou be submitted when available. Unplugged abandoned wells are to be included

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

54