submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices and Reports or	n Wells		
			5.	Lease Number NM- 03402
1.	Type of Well GAS	RECEIVED	6.	If Indian, All. or Tribe Name
2	No. 11 of O. 1114	OCT 2 2007	7.	Unit Agreement Name
2.	Name of Operator ConocoPhillips	Bureau of Land Management		•
	Conocornilles	Famington Field Office	0	San Juan 32-7 Unit
 3.	Address & Phone No. of Operator		 8.	Well Name & Number
	PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	San Juan 32-8 Unit #7M API Well No.
_				30-045-33307
4.	Location of Well, Footage, Sec., T, Sec., TN, RW, NMPM	R, M	10.	Field and Pool
Surf Unit H (SENE) 1875' FNL & 175' FEL, Sec. 21, T31N, R8W NMPM Bott Unit E (SWNW) 2140' FSL & 738' FWL, Sec.22, T31N, R8W NMPM			Blanco MV/Basin DK San Juan Co., NM	
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, Type of Submission Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection				OATA Other - Completion Detail RCVD OCT 4'07 OIL CONS. DIV. DIST. 3
	13. Describe Proposed or Complete	ed Operations		
Sec	e attached for completion detail and l	og.		
	. I hereby certify that the foregoing in the modern of the control	1	tle <u>Regulator</u> y	y Technician Date 10/1/07
AP	nis space for Federal or State Office use PROVED BY	Title		Date
Title	NDITION OF APPROVAL, if any: 18 U S C Section 1001, makes it a crime for any person knowing inted States any false, fictitious or fraudulent statements or repre-			

ACCEPTED FOR RECORD

COTO 3 :--7

FARENCE WE FIELD OFFICE

BY TELESTIN FIELD OFFICE

11/21/07 MIRU Weatherford Wireline. Start into well w/3.75" gauge ring. Ran GR/CCL/CBL log from8258' to 5650'. TOC @ 5904'. 7" shoe @ 3906'. Continued w/GR/CCL log to surface. RD Weatherford.

6/18/07 PT casing to 4100# 15/min – good test. Perf DK 8132' – 8236' @2spf, 8052' – 8110' @1spf; Frac:Pumped 30 bbls 2% KCL water, 10 bbls 15% HCL Acid, Slickwater w/40160# 20/40 TLC Sand.

7/5/07 BLM Notified on 5/9/07 that there was no overlap on the 4 ½" & 7" casing. TOC @ 5900' 7" shoe @ 3905'. 1995' short of cement to overlap. Proposing to squeeze and run a CBL. The Huerfanito Bentonite was found @ 4348'. Need to get to 4000' - This will be 50' above MV. Perfs will be @ 5185', top perf for MV. Squeeze will be @ 5730'. Verbal approval to proceed given.

7/5/07 MIRU BJ Cementers. MU RIH w/Weatherford CBP set @ 6100'. Shoot squeeze hole @ 5830'. RD Basin Wireline. PT CBP to 4100#. Pre-flush w/10 bbls H2O. Pumped 250 sx(495cf-88bbls) Type III Cement. Dropped plug & displaced w/90 bbls H2O. Release cementers. 7/7/07 MIRU Basin Wireline. RIH w/3.75" gauge ring to PBTD @ 5779' 51' above squeeze hole. RIH w/CBL Tool log from 5779' to 5300'. TOC is @ 5500'. RD wireline.

7/26/07 MIRU Basin Wireline. RIH w/squeeze perf gun. Shot 2 squeeze holes @ 5450'. RD wireline.

7/28/07 MIRU HES Cement. Pumped 300sx (414cf-74 bbls) Type III cement w/.3% Halad. Dropped plug & displaced w/84 bbls 2% KCL water. RD HES Cement.

9/11/07 MIRU Basin Wireline. RIH w/3.75" gauge ring to 5438'. Squeeze holes @ 5450'. RIH w/CBL/GR/CCL. Log from 5438' to 4900'. Est. TOC @ 5194'. RD Basin.

9/11/07 Called Wayne Townsend (BLM) & Henry Villanueva (OCD). 7" @ 3905'. PBTD @ 8290'. TOC from 2nd squeeze @ 5192'. Verbal approval to complete MV and no need to squeeze again Per Wayne Townsend. 300' coverage and only Lewis Shale is exposed.

9/17/07 Perf MV PLO 6026' – 5870' @ 1spf, LMF 5846' – 5726' @ 1spf; Frac: pumped 420 gal 15% HCL Acid, 60Q Slickfoam w/99324# 20/40 Brady Sand, total N2= 986800 SCF. UMF 5658' – 5565' @ 1SPF, CH 5658' – 5496' @ 1SPF; Frac: 60 Q Slickfoam w/54941# 20/40 Brady Sand. Total N2= 750000 SCF.

9/24/07 D/O CBP @ 6100'. Flow & blow well.

9/26/07 PU and ran 262 jts 2 3/8" 4.7# J-55 tubing set @ 8138'. Turned well over to production, waiting on facilities.