District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Is pit or below-grade tank covered by a "general plan"? Yes 🛛 No 🗌

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

Type of action: Registration of a pit o	r below-grade tank Closure of a pit or below-gra	de tank 🗵				
Operator: Chevron Production Co. Telephon	ne: (505) 334-7117 e-mail address:	MArcher@chevron.com				
Address: 322 County Road 3100, Aztec, NM 87410						
Facility or well name. Rincon #91 API #. 30-039-06	627 U/L or Qtr/Qtr <u>D</u> Sec	<u>11</u> T <u>26N</u> R <u>7W</u>				
County: Rio Arriba Latitude	36 50518 Longitude <u>-107 55029</u>	NAD: 1927 ⊠ 1983 □				
Surface Owner: Federal 🖾 State 🗌 Private 🔲 Indian 🗌						
<u>Pit</u>	Below-grade tank					
Type: Drilling ☐ Production ☑ Disposal ☐	Volume:bbl Type of fluid:					
Workover ☐ Emergency ☐	Construction material:					
Lined ☑ Unlined ☐	Lined ☑ Unlined ☐ Double-walled, with leak detection? Yes ☐ If not, explain why not.					
Liner type: Synthetic Thickness 2 Layers of 6mil plastic with thin						
fiberglass layer between Clay						
Pit Volume <u>5</u> bbl						
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)				
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)				
ingli water elevation of ground water.)	100 feet or more	(0 points) 0				
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)				
water source, or less than 1000 feet from all other water sources.)	No	(0 points) 0				
water sources, or less than 1000 feet from all other water sources.)	Less than 200 feet	(20 points)				
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)				
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(10 points) 20				
	Ranking Score (Total Points)	20				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	s relationship to other equipment and tanks. (2) Indic	ate disposal location (check the onsite box 1f				
your are burying in place) onsite offsite If offsite, name of facility	Envirotech's Landfarm #2 (3) Attach a general de	scription of remedial action taken including				
remediation start date and end date. (4) Groundwater encountered: No 🛛 Y	es 🔲 If yes, show depth below ground surface	ft. and attach sample results.				
(5) Attach soil sample results and a diagram of sample locations and excavat	ions					
Additional Comments:		78070				
Soil passed TPH standard of 100 ppm using USEPA Method 418 1 and the	100ppm OVM standard foot below lowest layer of					
Soil from inside the liner did not pass the TPH standard of 100 ppm and wa	as therefore removed.	/N AR & VE				
		LEIVE 5				
		O OI CUIS DIV DIST				
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guidelines	of my knowledge and belief. I further certify that t s 🔼, a general permit 🔲, or an (attached) alterna	he above-described pictor below-grade lank tive OCD-approved plan				
Date: 10-10-07	11/5/01	7000				
Printed Name/Title Mr. Michael W. Archer – HES Specialist	_Signature Mylace W	Clahy				
Your certification and NMOCD approval of this application/closure does n otherwise endanger public health or the environment. Nor does it relieve the regulations						
EPUTY OIL & GAS INSPECTOR, DISI. Printed Name/Title Signature	Date OCT 2 9 2	007				

CLIENT: Chevron	ENVIROTECH INC. ENVIROMENTAL SCIENTISTS & ENGINEERS 5796 U.S. HIGHWAY 64-9014 FARMINGTON, NEW MEXICO 87401	LOCATION NO:
FIELD REPORT:	CLOSURE VERIFICAT	ION PAGE No: of
OCATION: NAME. R: NC	WELL #. 9 PIT: WP: 26N RNG: 7-W PM: NM CNTY: LA	DATE STARTED. 08/30/67 DATE FINISHED. 09/76/107
QTR/FOOTAGE: \$28'N 100	2 W' CONTRACTOR.	ENVIRONMENTAL K: GCEV
ISPOSAL FACILITY:AND USE:	FT. x FT. DEEP. REMEDIATION LEASE: 5F 07 9 160 PIT LOCATED APPROXIMATELY 102	METHOD:
	TAREST WATER SOURCE > 1000 NEAREST	
MOCD RANKING SCORE: <u>20</u> nm :DIL AND EXCAVATION DE	BCD TPH CLOSURE STD: 100 PPM SCRIPTION:	CHECK ONE: PIT ABANDONED STEEL TANK INSTALLED
SCALE SCALE		REON DILUTION READING CALC ppm
0 FT 09/201/20	of duger 2 5g 20	PML 4:1 \$2 08
PIT PERIMETER	RESULTS	PIT PROFILE
© 220° }	SAMPLE FIELD HEADSPACE PID (ppm) 1	
	1 1 0.4 209/26 3.1 3 4 5	



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Chevron Production

Project #:

92270-170-027

Sample No.:

1

Date Reported:

9/28/2007

Sample ID:

Composite, Inside Lined Pit

Date Sampled: 8

8/30/2007

Sample Matrix:

Soil

Date Analyzed:

8/30/2007

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

1,300

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Rincon #91

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

Nicole Hayworth

Robin Kibler

Printe

Printed



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:	30-Aug-07

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	195	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Pal Ce	10-1-07
Analyst	Date
•	
Robin Kibler	
Printed	
Mical Hayrens	10/01/09
Review	Date
Nicole Hayworth	
Printed	



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Chevron Production

92270-170-027

Sample No.:

2

Date Reported:

Sample ID:

Discrete, 3' below Pit

9/28/2007

Sample Matrix:

Soil

9/26/2007

Preservative:

Cool

Date Analyzed: 9/26/2007 Analysis Needed: TPH-418.1

Project #:

Date Sampled:

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

8

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Rincon #91

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Robert Konig

Printed

Nicole Hayworth



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal	\neg	+~.
100	 IJά	100

Printed

26-Sep-07

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	220	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

J-1 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	10/02/07
Analyst	Date /
Robert Konig Printed	
Miral Hayron	10/02/07
Review	Date
Nicole Hayworth	

ENVI	ROT	ECH	INC.
COLUMN TO THE STREET			Mark Strain Control

Bill of Lading

PHONE: (505) 632-0615 • 5796 U.S. HIGHWAY 64 • FARMINGTON, NEW MEXICO 87401

MANIFEST # 28631

DATE 9-26-07 JOB #92270-170-027

LOAD	СОМ	ION OF SHIPME	ENT			TRANSPORTING COMPANY				
NO.	POINT OF ORIGIN	MATERIAL GRID YDS	BBLS	COMPANY			TIME DRIVER SIGNATUR			
(Modern Texico	BA <	Fridge			2		203	802)	Jim Bruttan
				E-13		2			6	
\										
276	Chloride test	1								
<u>0.10</u>	Paint filter test	j								
	Tum The 1831									
l certify	the material hauled from th									
JAME	t no additional materials hav		COMPANY /	oder	5 6	15 t	_ (CEF) SIGNATU	IRE J	or Br	ette
COMPA	NY CONTACT M. Ke	Dreyer	PHONE 505	5-320	<u>3 · 3 S</u>	49	DATE			