<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

office

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

	k covered by a "general plan"? Yes 🔯 No or below-grade tank 🔲 Closure of a pit or below-grade		
Address: <u>322 County Road 3100, Aztec, NM 87410</u> Facility or well name: <u>Rincon #44</u> API #: <u>30-039-06</u>		·	
Pit Type. Drilling ☐ Production ☒ Disposal ☐ Workover ☐ Emergency ☐ Lined ☒ Unlined ☐ Liner type: Synthetic ☐ Thickness 2 Layers of 6mil plastic with thin fiberglass layer between Clay ☐ Pit Volume _5_bbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If not	, explain why not.	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)	
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points) 0	
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points) 0	
	Ranking Score (Total Points)	0	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite for offsite for offsite, name of facility. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No Yes for offsite, show depth below ground surface. If the analysis of the sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: Soil passed TPH standard of 5000 ppm using USEPA Method 418.1 and the 100ppm OVM standard inside the pit and 3 feet below lowest layer of lines.			
		Se ASESTINO SA	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines. A general permit , or an (attached) alternative OCD-approved plan . Date 10-10-07 Printed Name/Title Mr. Michael W. Archer – HES Specialist Signature Signature for the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.			
Approval OCT 2 9 2007 Signature Signature Date:			

		i i						
CLIENT: Chevon		Env	IROTEC	H INC.		LOC	ATION N	D:
		5796	U.S. HIGHWAY	S & ENGINEERS 64-3014			C.O.C. N	lD:
92270-170-071		FARMIN PH	IGTON, NEW MI ONE: (505) 63:	EXICO 87401 2-0615				
FIELD REPOR	T:	CLOSU	RE V	ERIFIC	CATION	PAG	E No:	of
LOCATION: NAME. Ring QUAD/UNIT P SEC 2					v R A cm 1	— I	STARTED.	9-19-07
QTR/FOOTAGE: 690 /				: NOT CNI	1:1\1 21W		ONMENTAL ALIST. 2	LK/DNY
EXCAVATION APPROX	FT.	x F	T. x	FT. DE	EP. CUE	BIC YAR	DAGE: _	
DISPOSAL FACILITY:	•			REMEDIATI	ON METI	HOD:		
LAND USE:		LEASE	E: <u>570</u>	7932	F	ORMAT	ION:	
FIELD NOTES & REMAR DEPTH TO GROUNDWATER: 2100 NMOCD RANKING SCORE: 0	NEAR	EST WATER SE	QURCE: 210	700 N		ACE WATE	ECK ON	0-0 IE:
SOIL AND EXCAVATION	N DESC	RIPTION			-	1.7	ABANDON EL TANK	NED INSTALLED
10	X6 X 3	2			L			· · · · · · · · · · · · · · · · · · ·
¥			FIE	LD 418.1 CAL	_CULATIONS			
,	TIME		LAB No		1			CALC ppm
SCALE	13:10	comp	. 2	5	20 /	1	112	20
O FT	137.15	3'6" bel		3	G. 0	,	203	αυ
PIT PERIME	TER		OVM	~	PI'	ГPR	OFILE	1
TRAVEL NOTES								
TRAVEL NOTES. CALLOUT:			O	NSITE.				

36.540619

12:45-1:15

30-039-06857



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Chevron Production

Project #:

92270-170-071

Sample No.:

1

Date Reported:

9/21/2007

Sample ID:

Composite, Inside Lined Pit

Date Sampled:

9/19/2007

Sample Matrix:

Soil

Date Analyzed:

9/19/2007

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

	300	Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

44

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Rincon # 44

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

Robin Kibler

Drintad

Nicole Hayworth

Printed



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Chevron Production

2

Sample No.: Sample ID:

Discrete, 3' below Pit

Sample Matrix: Preservative:

Soil

Condition:

Cool

Cool and Intact

Project #:

92270-170-071

Date Reported:

9/21/2007

Date Sampled:

9/19/2007

Date Analyzed:

9/19/2007

Analysis Needed:

TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

20

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Rincon # 44

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

Nicole Hayworth

Robin Kibler

Printed

Printed



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal.	Date:	19-Sep-07
Oui.	Date.	13-0cp-01

Nicole Hayworth

Printed

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	203	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Pal Ke	9/21/07 Date
Robin Kibler Printed Review	<u>09/21/07</u> Date
neview	Date