

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE\*  
(See other instructions on reverse side)

FOR APPROVED  
OMB NO 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG\*

1a TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐

2 NAME OF OPERATOR  
ConocoPhillips

3 ADDRESS AND TELEPHONE NO  
PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements):  
At surface Unit P (SESE) 661' FSL, 1097' FEL

At top prod. interval reported below Same as above

At total depth Same as above

RECEIVED  
OCT. 23 2007

Bureau of Land Management

14. PERMIT NO. Farm DATE ISSUED

5 LEASE DESIGNATION AND SERIAL NO  
SF - 080854

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7 UNIT AGREEMENT NAME  
San Juan 32-8 Unit

8. FARM OR LEASE NAME, WELL NO.  
29M

9. API WELL NO.  
30-045-34075 - 0002

10. FIELD AND POOL, OR WILDCAT  
Blanco Mesa Verde

11 SEC., T., R., M., OR BLOCK AND SURVEY OR AREA  
Sec. 11 T31N R8W, NMPM  
RCVD OCT 26 '07  
OIL CONS. DIV.  
DIST. 3

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

15 DATE SPUNDED 7/5/07 16. DATE T.D. REACHED 7/13/07 17. DATE COMPL. (Ready to prod.) 10/15/07 18. ELEVATIONS (OF, RKB, RT, BR, ETC.) GL 6660' KB 6675'

20. TOTAL DEPTH, MD & TVD 8219' 21. PLUG, BACK T.D., MD & TVD 8215' 22. IF MULTIPLE COMPL., HOW MANY? 2 23. INTERVALS DRILLED BY ROTARY TOOLS yes CABLE TOOLS

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)\*  
Blanco Mesa Verde 5200' - 6090'

25. WAS DIRECTIONAL SURVEY MADE No  
26. TYPE ELECTRIC AND OTHER LOGS RUN Cement bond Log w/Gamma Ray Casing Collars 27. WAS WELL CORED No

| 28. CASING RECORD (Report all strings set in well) |               |                |           |                                 |               |
|----------------------------------------------------|---------------|----------------|-----------|---------------------------------|---------------|
| CASING SIZE/GRADE                                  | WEIGHT, LB/FT | DEPTH SET (MD) | HOLE SIZE | TOP OF CEMENT, CEMENTING RECORD | AMOUNT PULLED |
| 9 5/8" H-40                                        | 32.3#         | 245' 239'      | 12 1/4"   | surface; 180 sx (230 cf)        | 7 bbls        |
| 7" J-55                                            | 20#           | 3869'          | 8 3/4"    | surface; 630 sx (1284 cf)       | 60 bbls       |
| 4 1/2" J-55                                        | 10.5#, 11.6#  | 8218'          | 6 1/4"    | TOC 3000'; 330 sx (664 cf)      |               |

| 29. LINER RECORD |          |             |               |             | 30. TUBING RECORD |                |                 |
|------------------|----------|-------------|---------------|-------------|-------------------|----------------|-----------------|
| SIZE             | TOP (MD) | BOTTOM (MD) | SACKS CEMENT* | SCREEN (MD) | SIZE              | DEPTH SET (MD) | PACKER SET (MD) |
|                  |          |             |               |             | 2-3/8"            | 8148'          |                 |

31 PERFORATION RECORD (Interval, size and number)

@1SPF  
MF 5630' - 5872' = 17 holes  
PLO 5884' - 6090' = 13 holes  
CH 5200' - 5564' = 30 holes

32 ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

5630' - 6090' 60Q Slickfoam w/100700# 20/40 Brady Sand, tailed w/ 7300# 20/40 TLC. Total N2 = 1332200 SCF.  
5200' - 5564' 60Q Slickfoam w/99720 # 20/40 Brady Sand, tailed w/ 7300# 20/40 TLC. Total N2 = 1411900 SCF.

33. PRODUCTION  
DATE FIRST PRODUCTION SI PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump) Flowing WELL STATUS (Producing or shut-in) SI

DATE OF TEST 10/11/07 HOURS TESTED 1 CHOKE SIZE 1/2" PROD'N FOR TEST PERIOD OIL-BBL 189.75 mcf GAS-MCF .08 bw WATER-BBL  
FLOW TUBING PRESS. 1374# CASING PRESSURE 1324# CALCULATED 24-HOUR RATE OIL-BBL 4554 mcf/d GAS-MCF 2 bwpd WATER-BBL  
OIL GRAVITY-API (CORR.)

34 DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This will be a Basin Dakota/Blanco Mesa Verde well being DHC per order #2627AZ

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED [Signature] TITLE Regulatory Technician DATE 10/22/07

\*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

BLANCO MESA VERDE FIELD OFFICE  
BY [Signature]

|                      |       |       |
|----------------------|-------|-------|
| Ojo Alamo            | 2253' | 2346' |
| Kirtland             | 2346' | 2953' |
| Fruitland            | 2953' | 3564' |
| Pictured Cliffs      | 3564' | 3704' |
| Lewis                | 3704' | 4220' |
| Huerfanito Bentonite | 4220' | 4533' |
| Chacra               | 4533' | 5190' |
| Mesa Verde           | 5190' | 5567' |
| Menefee              | 5567' | 5880' |
| Point Lookout        | 5880' | 6229' |
| Mancos               | 6229' | 7177' |
| Gallup               | 7177' | 7909' |
| Greenhorn            | 7909' | 7959' |
| Graneros             | 7959' | 8063' |
| Dakota               | 8063' |       |

White, cr-gr ss.  
 Gry sh interbedded w/tight, gry, fine-gr ss.  
 Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.  
 Bn-Gry, fine grn, tight ss.  
 Shale w/siltstone stringers  
 White, waxy chalky bentonite  
 Gry fn grn silty, glauconitic sd stone w/drak gry shale  
 Light gry, med-fine gr ss, carb sh & coal  
 Med-dark gry, fine gr ss, carb sh & coal  
 Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation  
 Dark gry carb sh.  
 Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh  
 Highly calc gry sh w/thin lmst.  
 Dk gry shale, fossil & carb w/pyrite incl.  
 Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks

|                  |       |
|------------------|-------|
| Ojo Alamo        | 2253' |
| Kirtland         | 2346' |
| Fruitland        | 2953' |
| Pic.Cliffs       | 3564' |
| Lewis            | 3704' |
| Huerfanito Bent. | 4220' |
| Chacra           | 4533' |
| Mesa Verde       | 5190' |
| Menefee          | 5567' |
| Point Lookout    | 5880' |
| Mancos           | 6229' |
| Gallup           | 7177' |
| Greenhorn        | 7909' |
| Graneros         | 7959' |
| Dakota           | 8063' |

2000-

2000-2.5