

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a TYPE OF WELL. OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐		2 NAME OF OPERATOR ConocoPhillips		9 API WELL NO. 30-045-34098 - 0051	
b TYPE OF COMPLETION. NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐		3 ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700		10 FIELD AND POOL, OR WILDCAT Blanco MesaVerde	
4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface Unit P (SESE) 659' FSL, 936' FEL At top prod interval reported below Same as above At total depth Same as above		11 SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 4 T31N R8W, NMPM RCVD OCT 26 '07 OIL CONS. DIV.		12 COUNTY OR PARISH San Juan	
14. PERMIT NO.		DATE ISSUED		13 STATE New Mexico	
15. DATE SPUDDED 4/20/07	16. DATE T.D. REACHED 5/3/07	17. DATE COMPL. (Ready to prod.) 10/15/07	18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* GL KB 6632'	19 ELEV CASINGHEAD	
20. TOTAL DEPTH, MD & TVD 6275'	21 PLUG, BACK T.D., MD & TVD 6235'	22 IF MULTIPLE COMPL., HOW MANY* 1	23 INTERVALS DRILLED BY yes	24 PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco MesaVerde 5184' - 6108'	
25. TYPE ELECTRIC AND OTHER LOGS RUN Cement bond Log w/Gamma Ray Casing Collars			26 WAS WELL CORED No		
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8" H-40	32.3#	231'	12 1/4"	surface; 76 sx (122 cf)	5 bbls
7" J-55	20#	3238'	8 3/4"	surface; 530sx (1089 cf)	54 bbls
4 1/2"	10.5#, 11.6#	6246'	6 1/4"	TOC 3100'; 250 sx (505 cf)	
29. LINER RECORD			30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	PACKER SET (MD)
				2-3/8"	5837'
31 PERFORATION RECORD (Interval, size and number)			32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
@1SPF LMF 5630' - 5820' PLO 5862' - 6108' CH 5184' - 5524' UMF 5544' - 5584' Lewis 4712' - 5142'			5630' - 6108' 10 bbls 15% HCL Acid, 60Q Slickfoam w/99600# 20/40 AZ Sand, total N2= 1238400 SCF. 5184' - 5584' 10 bbls 15% HCL Acid, 60Q Slickfoam w/100000# 20/40 AZ Sand, total N2= 1161300 SCF. 4712' - 5142' 10 bbls 15% HCL Acid, 75Q 20# Linear Gel foam w/ 200000# 20/40 AZ Sand, total N2= 1522700 SCF.		
33. PRODUCTION					
DATE FIRST PRODUCTION SI W/O Facilities		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing			WELL STATUS (Producing or shut-in) SI
DATE OF TEST 10/15/07	HOURS TESTED 1	CHOKE SIZE 1/2"	PROD'N FOR TEST PERIOD Oil-BBL	GAS-MCF 64.63 mcf	WATER-BBL .21 bw
FLOW TUBING PRESS 667#	CASING PRESSURE 656#	CALCULATED 24-HOUR RATE 1551 mcf	GAS-MCF 5 bwpd	OIL GRAVITY-API (CORR.)	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold					TEST WITNESSED BY
35. LIST OF ATTACHMENTS This is a standalone MesaVerde well.					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records					

SIGNED Regulatory Technician TITLE Regulatory TechnicianDATE 10/22/07

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

FARMINGTON FIELD OFFICE
BY T. Salyers

204/02 JT

Ojo Alamo	2294'	2366'	White, cr-gr ss.
Kirtland	2366'	3197'	Gry sh interbedded w/tight, gry, fine-gr ss.
Fruitland	3197'	3524'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.
Pictured Cliffs	3524'	3664'	Bn-Gry, fine grn, tight ss.
Lewis	3664'	4317'	Shale w/siltstone stringers
Huerfanito Bentonite	4317'	4711'	White, waxy chalky bentonite
Chacra	4711'	5167'	Gry fn grn silty, glauconitic sd stone w/drak gry shale
Mesa Verde	5167'	5527'	Light gry, med-fine gr ss, carb sh & coal
Menefee	5527'	5858'	Med-dark gry, fine gr ss, carb sh & coal
Point Lookout	5858'		Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation

1200-

204-0102 JT

Ojo Alamo	2294'
Kirtland	2366'
Fruitland	3197'
Pic.Cliffs	3524'
Lewis	3664'
Huerfanito Bent.	4317'
Chacra	4711'
Mesa Verde	5167'
Menefee	5527'
Point Lookout	5858'