This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

cation of Well	: Unit Lo	etter _	G	Sec	16	Twp _	025N	Rg	е	004W AP	l #	30-039-06018	
Name of Reservoir or Pool				Type of Prod				Method of Prod			Prod Medium		
Upper Completion	PC	Gas				Flow			Tubing				
Lower Completion	MV	Oil				Artificial Lift			Casing				
Completion						X							
				Pre	-Flow S						-,		
Upper Completion Hour, Date, Shut-In 8/27/2007				Length of Time Shut-In 129 hours				SI Press. PSIG Flow		Stal	Stabilized?(Yes or No) Yes		
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
	8/27/2007				9 hours				Artificial Lift			Yes	
		0007.0	00.00.44		Flo	w Test							
Commenced at	t: 8/2//			l			one Pro			or Lower): Lo	ower_		
Time (date/time)		Lapsed Time Since*		Upp	PRESS Upper zone				d Zone perature		Remarks		
8/27/2007 9:00:00 AM 0			0	`	89	9	92			Both zones shut in			
8/28/2007 9:00:00 AM		24			121	5	70			Both zones shut in			
8/29/2007 9:00:00 AM		48			125	5	96	Both zones shu		in			
8/30/2007 9:00:00 AM		72			127		03			Both zones shut in			
8/31/2007 9:00:00 AM		96			127		86		Flow MV zone				
9/1/2007 9:00:00 AM 120			120		127	, 88		Flow MV zo		Flow MV zone	ne '		
roduction rate	during te	est									f	·.	
il:BPOD Based on:Bbl				bls. InHrs.			Grav.				GOR		
as		MC	FPD; Tes	t thru (Or	ifice or M	leter) _							
				Mi	d-Test S	hut-In	Pressu	re Data					
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Sta	Stabilized?(Yes or No	
Lower Completion					Length of Time Shut-In				SI Press. PSIG		Sta	Stabilized?(Yes or No)	
				(Continue on reverse side)			side)		345	678	970772000 IVED 435		

Flow Test No. 2

Commenced at:			Zone Producing (Upper or Lower)						
Time	Lapsed Time	PRES	SURE	RE Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature)	Remarks			
		_							
				1					
	``								
٠									
Production rate dur	ring test								
Oil:BF	POD Based on:	Bbls. In	Hrs.		Grav.	GOR			
Gas	MCFPD; Test t	hru (Orifice or M	leter)						
Remarks:						l			
Nemano.									
							\		
I hereby certify that	t the information herein o	contained is true	and complete	to the best o	f my knowled	ge.			
Approved: 'Ñ	DV 1 2 2007	20	Opera	tor: Conocc	Phillips Inc.				
	Conservation Division	Ву:	Travis Chav	/ez					
A I lawrence				Title: Multi-Skilled Operator					
Dy. / ' '	uty Oil & Gas Insp	ector.	Title:	Multi-Skilled	operator				
Title:	District #3		Date:	Friday, Octo	ober 05, 2007	,			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours
- 5 Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests: mmediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one presure measurement immediately prior to the conclusion of each flow period. 7-day tests. immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)