This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Burlin	igton Re	sources	; Oil & Gas (Co.	Leas	e Name	SAN	JUAN 2	7-5 UN	IT		Well No52	
Location of Wel	l: Unit l	_etter _	<u>M</u> S	ec	04	Twp	027N	R	ge	005W	API :	# 30-039-07155	
	Name of Reservoir or Pool				Type of Prod				Method of Prod			Prod Medium	
Upper Completión	PC				Gas				Flow			Tubing	
Lower Completion	MV				Gas				Artificial Lift			Tubing	
Pre-Flow Shut-In Pressure Data													
Upper	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
Completion	8/10/2007				81 hours				365		365	Yes	
Lower	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
Completion 8/10/2007				130 hours				124			Yes		
					Flo	w Test	No. 1					, '	
Commenced a	it: 8/13	/2007 9:	20:00 AM			Zd	one Pro	oducing	(Upper	or Lower):	Upp	per	
Time Lapsed Time				PRESSURE				Prod Zone					
(date/time)		1		Uppe	er zone Lower zone		Temperature			Remarks			
8/14/2007 9:33:33 AM 24			1	22	12	24							
8/15/2007 10:52:05 AM 49				92 124				blew upper zone 2			20% curve was met. Lower zo		
Production rate	during t	est											
Oil:	BPOD Based on:Bbls			Bbls	s. InHrs				Grav.			GOR	
Gas		MC	FPD; Test th	ıru (Orifi	ice or N	/leter)							
			ı	. Miq	-Toet S	Shut-In F	Praeeii	re Data		•		*	
Unner	Upper Hour, Date, Shut-In Completion				d-Test Shut-In Pressure Dat Length of Time Shut-In			ie Data	SI Press. PSIG			Stabilized?(Yes or No)	
												. *	
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	

(Continue on reverse side)



Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)					
Time	Lapsed Time	PRES	SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks	`			
-									
Production rate during	test .								
Oil:BPOD Based on:Bbls			Hrs.		GravGOR				
GasMCFPD; Test thru (Orifice or Meter)									
Remarks:									
I hereby certify that the information herein contained is true and complete to the best of my knowledge.									
Approved:	NOV 1 6 2007	20	Operat	Operator: Burlington Resources Oil & Gas Co.					
New Mexico Oil Co	onservation Division		Ву:	By: Julian Montoya					
By:		Title: _	Multi-Skilled Operator						
Title:	outy Oil & Gas Ins	poetor	Date:	Date: Tuesday, November 13, 2007					

Deputy Oil & Gas Inspector,

District #GRTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of a noil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- $6\,$ $\,$ Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test.No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above