

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS IN
NORTHWEST NEW MEXICO

OPERATOR: Williams Production Company LOCATION: J 19 31 4 LEASE NUMBER: SF-078889

NAME OF WELL/WELLS OR PIPELINE SERVICED: ROSA UNIT #043 DK
DUALWELL N/A

30-039-07954

ELEVATION: 6572' GR COMPLETION DATE: 10/20/87 TOTAL DEPTH: 500 ft. LAND TYPE: FED

CASING: 7-5/8" 26.4# K-55 Set @ N/A ft. Casing is not cemented.

CEMENT PLUG--Top:N/A' Bottom: N/A' Used 0 sx. Class "B" (1.18 cu.ft./sk).

WATER DEPTH: 80 ' Water zone thickness not available. WATER DESCRIPTION: Fresh

DEPTH OF GAS: N/A '

COKE: 6345 lbs. of Metalurgical coke breeze used.

NUMBER & TYPE OF ANODES: 10-D TOP ANODE @ 315 ft. BOTTOM ANODE @ 440 ft.

VENT PIPE: 1" PVC Set @ 500 ft. Vent pipe perforated from 295 ft. to 500 ft.

REMARKS: _____

Top of Cement @ N/A'

Casing @ N/A'

Bottom of Cement @ N/A'

Top Anode @ 315'

10-D Anodes

Bottom Anode @ 440'

Perforated Vent Pipe

6-3/4" Hole to 500'

RECEIVED
DEC 11 1991.
OIL CON. DIV.
DIST. 3

LOCATION

Road #43

DATE

8-11-87

10	130 1.51	250 1.07	370 1.17	490
15	135 1.21	255 .81	375 1.41	495
20	140 1.23	260 1.05	380 1.35	500
25	145 1.09	265 .91	385 1.10	505
30	150 .79	270 .87	390 1.22	510
35	155 1.14	275 .85	395 1.33	
40	160 1.33	280 .83	400 1.51	
45	165 1.33	285 .91	405 1.28	
50	170 1.28	290 .92	410 1.24	
55	175 1.41	295 .76	415 1.41	
60	180 1.48	300 .87	420 1.27	
65	185 1.39	305 .88	425 .93	
70	190 1.36	310 1.25	430 1.05	
75	195 1.09	315 1.40	435 1.37	
80 1.08	200 1.07	320 1.15	440 1.46	
85 1.09	205 1.17	325 1.39	445 1.70	
90 1.06	210 1.38	330 1.25	450 1.82	
95 1.23	215 1.47	335 1.26	455 1.98	
100 1.26	220 1.62	340 1.38	460 1.85	
105 1.35	225 1.57	345 1.20	465 1.76	
110 1.27	230 1.55	350 1.26	470 1.72	
115 1.0	235 1.45	355 1.24	475 1.68	
120 1.30	240 1.19	360 1.40	480 1.57	
125 1.48	245 1.08	365 1.44	485	

Mud

Total Amps 13.3

Total Volts 10.46

Total Res. .78

CAVING trouble
Had to pull
Anodes up.

LOCATION Rosa #43

DATE 8-11-87

10	130 1.51	250 1.07	370 1.17	490
15	135 1.21	255 .81	375 1.41	495
20	140 1.23	260 1.05	380 1.35	500
25	145 1.09	265 .91	385 1.10	505
30	150 .79	270 .87	390 1.22	510
35	155 1.14	275 .85	395 1.33	
40	160 1.33	280 .88	400 1.51	
45	165 1.33	285 .91	405 1.28	
50	170 1.28	290 .92	410 1.24	
55	175 1.41	295 .76	415 1.41	
60	180 1.48	300 .87	420 1.27	
65	185 1.39	305 .88	425 .93	
70	190 1.36	310 1.25	430 1.05	
75	195 1.09	315 1.40	435 1.37	
80 1.08	200 1.07	320 1.15	440 1.46	
85 1.09	205 1.17	325 1.39	445 1.70	
90 1.06	210 1.38	330 1.25	450 1.82	
95 1.23	215 1.47	335 1.26	455 1.98	
100 1.26	220 1.62	340 1.38	460 1.85	
105 1.35	225 1.57	345 1.20	465 1.76	
110 1.27	230 1.55	350 1.26	470 1.72	
115 1.0	235 1.45	355 1.24	475 1.68	
120 1.30	240 1.19	360 1.40	480 1.57	
125 1.48	245 1.08	365 1.44	485	

} Mud

Total Amps 13.3
 Total Volts 10.46
 Total Res. .78

Causing trouble
 Had to pull
 Anodes up.