

30-045-21827

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Mesa Operating Ltd. Partnership Location: Unit D Sec. 6 Twp 31N Rng 10W

Name of Well/Wells or Pipeline Serviced Primo Federal 1A (MV, PC, CH)

Elevation _____ Completion Date _____ Total Depth 200' Land Type* F

Casing, Sizes, Types & Depths No Record

If Casing is cemented, show amounts & types used No Record

If Cement or Bentonite Plugs have been placed, show depths & amounts used
No Record

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 60'

RECEIVED

APR 30 1990

Depths gas encountered: No Record

OIL CON. DIV.
DIST. 3

Type & amount of coke breeze used: 1200# Coke Breeze

Depths anodes placed: 185' - 175' - 165' - 155' - 145' - 135' - 125' - 115' - 105' - 95'

Depths vent pipes placed: No Record


Vent pipe perforations: No Record

Remarks: Type of Anodes used CD-51

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

OPERATOR: <i>Mass Petroleum Company</i>			
FIELD:		LEASE: <i>Primo Federal</i>	WELL NO. <i>1A</i>
FINAL CHECK Polarity	Date <i>3/4/76</i>	RECTIFIER DATA: Model Setting: <i>116</i> Volts	Ser. No. <i>124</i> Amps



POTENTIALS AT INSULATING FLANGE				GROUNDBED DESCRIPTION			
Rectifier	On	Off	No. & Type of Anodes <i>10-CD-51</i>				
Well Head			Horizontal Vertical ☒				
			Backfill <i>100# C&G concrete</i>				
Depth, Moisture <i>60</i>		Holes <i>1</i>		Total Hole Depth <i>200</i>			
Log Anode	Dept.	Log Anode	Dept.	Anode Placement			
<i>1.6</i>	<i>70</i>	<i>1.7</i>	<i>110</i>	<i>1</i>	<i>185</i>		
<i>1.6</i>	<i>75</i>	<i>1.8</i>	<i>125</i>	<i>2</i>	<i>175</i>		
<i>1.5</i>	<i>80</i>	<i>1.9</i>	<i>130</i>	<i>3</i>	<i>165</i>		
<i>1.9</i>	<i>85</i>	<i>1.9</i>	<i>135</i>	<i>4</i>	<i>155</i>		
<i>1.9</i>	<i>90</i>	<i>1.4</i>	<i>140</i>	<i>5</i>	<i>145</i>		
<i>1.6</i>	<i>100</i>			<i>6</i>	<i>135</i>		
<i>1.1</i>	<i>110</i>			<i>7</i>	<i>125</i>		
<i>1.9</i>	<i>115</i>			<i>8</i>	<i>115</i>		
<i>1.8</i>	<i>120</i>			<i>9</i>	<i>105</i>		
<i>1.8</i>	<i>125</i>			<i>10</i>	<i>95</i>		
<i>1.7</i>	<i>130</i>						
<i>1.7</i>	<i>135</i>						
<i>1.6</i>	<i>140</i>						
<i>1.6</i>	<i>145</i>						
<i>1.4</i>	<i>150</i>						
<i>1.5</i>	<i>155</i>						
<i>1.1</i>	<i>160</i>						
<i>1.0</i>	<i>165</i>						

CORROSION CONTROL COMPANY
Aztec, New Mexico 87410

Installation Record