

#3 30-045-11751

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit A Sec. 15 Twp 32 Rng 12

Name of Well/Wells or Pipeline Serviced _____

Hubbard #3

Elevation — Completion Date 8/18/95 Total Depth 391' Land Type P

Casing Strings, Sizes, Types & Depths 8/17 Set 98' of 8" PVC Casing.

No Gas, Water, or Boulders were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

With 22 Sacks.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 125'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 391' DEPTH.

Used 95 SACKS OF ASBURY 218R (4750#)

Depths anodes placed: 375', 360', 350', 340', 330', 320', 305', 255', 245', 235', 225', 215', 205', 170', & 140'.

Depths vent pipes placed: SURFACE TO 391'.

Vent pipe perforations: BOTTOM 260'.

Remarks: _____

RECEIVED
JAN 11 1996

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.