

#5R 30-045-28958

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit B Sec. 16 Twp 32 Rng 07

Name of Well/Wells or Pipeline Serviced _____

Allison #5R

Elevation 6510 Completion Date 12/17/93 Total Depth 405' Land Type S

Casing Strings, Sizes, Types & Depths 12/16 Set 99' of 8" PVC Casing.

NO WATER, GAS, or Boulders were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 25 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 125'. A WATER

SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 405' Depth.

Used 54 SACKS OF ASBURY 218R, AND 27 SACKS OF LOTESCO^{SW} (5400#)

Depths anodes placed: 385', 370', 355', 340', 327', 300', 285', 275', 250', 230', 215', 195', 175', 165', + 157'.

Depths vent pipes placed: SURFACE TO 405'.

Vent pipe perforations: BOTTOM 290'.

Remarks: _____

RECEIVED
IN JAN 11 1996

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.