

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Sundry Notices and Reports on Wells

RCVD DEC 13 '07

OIL CONS. DIV.

DIST. 3

1. Type of Well

Oil

RECEIVED

DEC 11 2007

Bureau of Land Management  
Farmington Field Office

2. Name of Operator

EnerVest Operating LLC

3. Address & Phone No. of Operator

210 N. Auburn, Farmington, NM 87401

Location of Well, Footage, Sec., T, R, M

790' FSL & 1770' FWL, Section 36, T-26-N, R-3-W

5. Lease Number

Jicarilla Apache A 118

6. If Indian, All. or  
Tribe Name

Jicarilla Apache

7. Unit Agreement Name

8. Well Name & Number

Jicarilla Apache A118 #11

9. API Well No.

30-039-23558

10. Field and Pool

NE Ojito GI/Dk

11. County & State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other - Return to Production

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

EnerVest Operating LLC plugged and abandoned the referenced well per the attached P&A report. 11/1/07

14. I hereby certify that the foregoing is true and correct.

Signed

Mickey Aherns

Title

Prod. Foreman

Date

12-6-07

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

DEC 12 2007

FARMINGTON FIELD OFFICE

NMOCD

# A-PLUS WELL SERVICE, INC.

P.O. BOX 1979

Farmington, New Mexico 87499

505-325-2627 \* fax: 505-325-1211

EnerVest

Jicarilla Apache A118 #11

November 1, 2007

Page 1 of 1

790' FSL & 1770' FWL, Section 36, T-26-N, R-3-W

Rio Arriba County, New Mexico

Lease Number: Jicarilla Contract A 118

API # 30-039-23558

## Plug & Abandonment Report

Notified BLM – JAT and NMOCD on 10/29/07

### Work Summary:

10/29/07 MOL & RU. Open well, no pressure. ND wellhead. NU BOP, test. Pull up on donut. POH and tally 48 stands. Shut in well. SDFD.

10/30/07 Open well, no pressure. POH with 221 joints 2.375" tubing, 7003'. TIH with 4' plugging sub, SN with standing valve. Tag existing CIBP at 7054'. Pressure test tubing to 500 PSI at 3500' and 7054', held OK for 5 minutes. RIH with fishing tool to standing valve. POH with sandline, tool and standing valve. Load hole with ¼ bbl of water. Pressure test bradenhead to 400 PSI, held OK for 10 minutes. Load casing with 4 bbls of water. Pressure test casing to 800 PSI, held OK for 10 minutes.

**Plug #1** with existing CIBP at 7054', spot 16 sxs Type III cement (22 cf) inside casing from 7054' up to 6986' to isolate the Dakota and Gallup intervals.

PUH to 5611'. Load hole with 2.5 bbls of water.

**Plug #2** spot 16 sxs Type III cement (22 cf) inside casing from 5611' up to 5453' to cover the Mesaverde top.

PUH to 3964'. Shut in well. SDFD.

10/31/07 Open well, no pressure. Load hole with 5 bbls of water.

**Plug #3** spot 61 sxs Type III cement (81 cf) inside casing from 3964' up to 3362' to cover the Pictured Cliffs, Fruitland, Kirtland and Ojo Alamo tops.

PUH to 2284'. Load hole with 3 bbls of water.

**Plug #4** with 18 sxs Type III cement (24 cf) inside casing from 2284' up to 2106' to cover the Nacimiento top.

PUH to 380'. Load hole with 3 bbls of water.

**Plug #5** mix and pump 63 sxs Type III cement (84 cf) down the 5.5" casing from 380' to surface, circulate good cement out the casing valve.

TOH and LD all tubing. ND BOP. Begin to dig out wellhead. Pulled boards out with winch to dig out wellhead. Issue Hot Work Permit. Cut off wellhead. Found cement down 40' in the 5.5" casing and 8.625" annulus. Procedure change approved by B. Hammond, BLM – JAT representative. RD rig and equipment.

**Plug #6** mix and pump 83 sxs Type III cement (110 cf) to fill the casing and annulus. Install P&A marker. Fill up cellar with cement. SDFD.

11/01/07 RD and MOL. Road rig and equipment to A+ yard.

B. Hammond, BLM – JAT representative, was on location.