Submit 3 Copies To Appropriate District  State of New Me	
Office Energy, Minerals and Natur	
1625 N French Dr., Hobbs, NM 87240 District II OIL CONSERNATION	WELL API NO. 30-039-30148
1301 W Grand Ave. Artesia NM 88210 OIL CONSERVATION	V DI VISION
District III 1000 Rio Brazos Rd., Aztec, NM 87410  1220 South St. Fra Santa Fe, NM 8	meis Di.
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gaz (Lease No. 11 'OB
	OIL CONS. DIV.
SUNDRY NOTICES AND REPORTS ON WEL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-10 PROPOSALS.)	OR PLUG BACK TO A Carracas SWD DIST. 3
1. Type of Well: Oil Well Gas Well Other SwD-16	8. Well Number RCVD JAN 11'08
2. Name of Operator	9. OGRID Number
Energen Resources Corporation	162928
3. Address of Operator	10. Pool name or Wildcat
2198 Bloomfield Highway, Farmington, NM 87401	Entrada-Chinle
4. Well Location	
Unit Letter I : 1489 feet from the South line and 134 feet from the East line	
	Range 04W NMPM County Rio Arriba
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6222' GL	
Pit or Below-grade Tank Application 🗵 or Closure 🗆	
Pit typeDrill_ Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water	
Pit Liner Thickness: 12 mil Below-Grade Tank: Volumebbls; Construction Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:	
	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS. PLUG AND
PULL OR ALTER CASING MULTIPLE COMPLETION	CASING TEST AND ABANDONMENT CEMENT JOB
OTHER:	OTHER: set liner X
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
12/28/07 TD:9334' PBTD:9280' Drill 6.25" hole to 9334'. Run 79 jts. 5.50" 17# N-80 production liner, set @ 9315'. TOL:5944'. RU Halliburton. Cement with 375 sks 50/50 poz, 35% SSA, 0.6% SCR-100, 0.4%	
Halad-413, 5#/sk gilsonite, 1/4#/sk flocele tailed by 200 sks Class G, 6% SCR-100, 0.4% Halad-413, 35%	
SSA, 0.3% CFR, 5#/sk gilsonite, 1/4#/sk flocele (1015 cu.ft.). Did not plug down because of liner hanger	
disengagement. Did not circulate. Will <u>run CRL</u> . Will repair top of liner during completion. 01/03/08 Ran CBL. TOC @ 8000!	
01/05/08 Ran 92 jts. 2.375" tubing, set @ 2998'. ND BOP. Release rig.	
01, 05, 00 Ital 32 Jan. 2.575 Catalog, Sec e 2550 . I	e bit. Neichbe 11g.
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit or an (attached) alternative OCD-approved plan	
SIGNATURE WILL DOWN TITLE	
Type or print name Vicki Donaghey E-m	nail address: vdonaghe@energen.com Telephone No. 505.325.6800
For State Use Only / Deputy Oil & Gas Inspector,	
APPROVED BY H. Villanueva TIT	District #3 DATE JAN 1 1 2008
Conditions of Approval, if any:	