

30-039-07720

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec 34 Twp 30 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JAUN 30-6 UNIT #99

cps 288w

Elevation 6230' Completion Date 7/23/69 Total Depth 520' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 85' TO 95'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

CON. DIV.
DIST. 3

Type & amount of coke breeze used: 8760 lbs.

Depths anodes placed: 486', 480', 470', 440', 422', 416', 410', 370', 350'

Depths vent pipes placed: 486' OF 3/4" HOSE

Vent pipe perforations: 425'

Remarks: gb #2 PLASTIC MOLD USED TO CAP ANODES. DID NOT USE SHRINK SLEEVE ON WIRE.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

5'18" insert 201 = 130'

Drilling Log (Attach Hereto) ☒

GROUND BED #2

Completion Date 7-23-69

Well Name SJ 30-6 #99		Location SW 34-30-7		CPS No. 288 W	
Type & Size Bit Used 7 7/8 EU 170 = 520 - 5" 2278 = 250, 5" 75664 = 140				Work Order No. 184-52624-50-20	
Anode Hole Depth 520	Total Drilling Rig Time 49 Hrs.	Total Lbs. Coke Used 8760	Lost Circulation Mat'l Used 0	No. Sacks Mud Used 1	
Anode Depth					
# 1 486	# 2 480	# 3 470	# 4 440	# 5 422	# 6 416
# 7 410	# 8 370	# 9 350	# 10		
Anode Output (Amps)					
# 1 3.1	# 2 3.6	# 3 3.2	# 4 2.4	# 5 2.6	# 6 3.1
# 7 3.0	# 8 2.9	# 9 2.8	# 10		
Anode Depth					
# 11	# 12	# 13	# 14	# 15	# 16
# 17	# 18	# 19	# 20		
Anode Output (Amps)					
# 11	# 12	# 13	# 14	# 15	# 16
# 17	# 18	# 19	# 20		
Total Circuit Resistance		No. 8 C.P. Cable Used		No. 2 C.P. Cable Used	
Volts 13.5	Amps 10.5	Ohms 1.28	4172	4022 on Anodes, 150 Surface	

Remarks: 3/4" Hose to No. 1 Anode - Perforated 425'
50 lbs Borafos used

Plastic mold used to Cap Anodes - Did Not use
Shrink Sleeve on wire.

Copy of this Report
in Rectifier

All Construction Completed

Amels
(Signature)

GROUND BED LAYOUT SKETCH



