

30045-11364

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit H Sec. 21 Twp 32 Rng 09

Name of Well/Wells. or Pipeline Serviced _____

S.J. 32-9 # 70X

Elevation 6909 Completion Date 7/14/94 Total Depth 428' Land Type F

Casing Strings, Sizes, Types & Depths 7/13 SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used CEMENTED

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT A DAMP ZONE AT 100' AND SOME WATER

AT 315' A WATER SAMPLE WAS TAKEN. WATER WAS FRESH.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 428' DEPTH.

USED 110 SACKS OF ASBURY 218R (5500#)

Depths anodes placed: 405', 395', 386', 375', 365', 355', 347', 339', 331', 310', 254', 245', 236', 209', + 201'

Depths vent pipes placed: SURFACE TO 428'

Vent pipe perforations: BOTTOM 300'

Remarks: _____

RECEIVED
R JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.