

1476

E

30-045-25005

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL INC. Location: Unit F Sec. 27 Twp 30 Rng 13Name of Well/Wells or Pipeline Serviced MC GEE #1E

cps 620lw

Elevation N/A Completion Date 1/3/87 Total Depth 300' Land Type* N/ACasing, Sizes, Types & Depths N/AIf Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 80' & 150'Depths gas encountered: N/AType & amount of coke breeze used: 1800 lbsDepths anodes placed: 290', 280', 270', 260', 250', 240', 230', 220', 210', 200'Depths vent pipes placed: N/AVent pipe perforations: N/ARemarks: gb #1

RECEIVED
MAY 31 1991
OIL CONSERVATION DIV.
OIL CONSERVATION DIV.
DIST. DIV.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

BURGE CORROSION SYSTEMS, INC.

P.O. BOX 1359 - PHONE 334-6141
AZTEC, NEW MEXICO 87410

Drilling Log (Attach Hereto). ☐

6201W

Completion Date 1-3-87

Well Name <i>Mc Gee # 1E</i>				Location <i>Union Texas Petroleum</i>					
Type & Size Bit Used								Work Order No. <i>133</i>	
Anode Hole Depth <i>300</i>		Total Drilling Rig Time		Total Lbs. Coke Used <i>1800</i>		Lost Circulation Mat'l Used		No. Sacks Mud Used	
Anode Depth	#1 <i>290</i>	#2 <i>280</i>	#3 <i>270</i>	#4 <i>260</i>	#5 <i>250</i>	#6 <i>240</i>	#7 <i>230</i>	#8 <i>220</i>	#9 <i>210</i>
Anode Output (Amps)	#1 <i>2.2</i>	#2 <i>2.3</i>	#3 <i>2.1</i>	#4 <i>1.8</i>	#5 <i>2.0</i>	#6 <i>1.4</i>	#7 <i>2.2</i>	#8 <i>1.4</i>	#9 <i>1.3</i>
Anode Depth	#11	#12	#13	#14	#15	#16	#17	#18	#19
Anode Output (Amps)	#11	#12	#13	#14	#15	#16	#17	#18	#19
Total Circuit Resistance						No. 8 C.P. Cable Used <i>2650</i>		No. 2 C.P. Cable Used	
Volts <i>12.1</i>	Amps <i>6.48</i>	Ohms <i>1.87</i>							

Remarks: *Negative 321 feet*

All Construction Completed

John Smith
(Signature)

GROUND BED LAYOUT SKETCH



