

30-045-09977

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit A Sec. 03 Twp 30 Rng 11

Name of Well/Wells or Pipeline Serviced _____

Callaway, Zella #1

Elevation _____ Completion Date 6/23/94 Total Depth 434' Land Type P

Casing Strings, Sizes, Types & Depths 6 1/4 Set 99' of 8" PVC Casing.

No Gas or Water, But 32' of Boulders, were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

With 26 Sacks.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Placed a 24' Plug (91'-115'). Used 8 Sacks of Cement.

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 150'. A WATER

SAMPLE WAS TAKEN.

Depths gas encountered: 425'

Ground bed depth with type & amount of coke breeze used: 434' Depth.

Used 112 Sacks of Asbury 218R (5600#)

Depths anodes placed: 415', 395', 385', 368', 361', 354', 347', 325', 313', 306', 299', 292', 202', 195', + 188'.

Depths vent pipes placed: SURFACE TO 434'.

Vent pipe perforations: BOTTOM 310'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.