

30-045-22909

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit M Sec. 13 Twp 31 Rng 10

Name of Well/Wells. or Pipeline Serviced _____

S.J. 32-9 #82

Elevation 6365 Completion Date 8/3/94 Total Depth 409' Land Type F

Casing Strings, Sizes, Types & Depths 8/2 Set 100' of 8" PVC Casing.

NO GAS, WATER, or Boulders Were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented
WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 120' AND MORE
FRESH WATER AT 330'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 409' DEPTH.
USED 104 SACKS OF ASBURY 218R (5200#)

Depths anodes placed: 370', 363', 356', 349', 342', 310', 302', 295', 193', 186', 179', 172', 165', 158', + 138'

Depths vent pipes placed: SURFACE TO 409'.

Vent pipe perforations: BOTTOM 290'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.