

30-045-22926

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit E Sec. 24 Twp 30 Rng 09

Name of Well/Wells or Pipeline Serviced _____

Riddle A #3A

Elevation 5732 Completion Date 7/1/94 Total Depth 328' Land Type F

Casing Strings, Sizes, Types & Depths 6/29 Set 99' of 8" PVC Casing.

NO GAS OR WATER, BUT 12 (6-12) OF BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Used 5 SACKS OF CEMENT, TO PLACE A 15' (100'-115') Plug, TO STOP ARTESIAN WATER.

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 130', AND MORE

FRESH WATER AT 265'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE.

Ground bed depth with type & amount of coke breeze used: 328' Depth.

Used 75 SACKS OF Asbuty 218R (3750#)

Depths anodes placed: 294', 286', 278', 270', 234', 226', 218', 210', 202', 194', 186', 178', 156', 148', & 140'

Depths vent pipes placed: SURFACE TO 328'.

Vent pipe perforations: BOTTOM 210'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.