

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144
June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☐ No ☒


Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator: Dugan Production Corp Telephone: (505)325-1821 e-mail address: _____
Address: P.O. Box 420, Farmington, New Mexico 87401
Facility or well name: Silver Medal No. 1 API #: 30-045-26034 U/L or Qtr/Qtr M Sec 27 T 24N R 10W
County: San Juan Latitude 36.27905 Longitude 107.89049 NAD: 1927 ☐ 1983 ☐ Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

<u>Pit</u>	<u>Below-grade tank</u>
Type: Drilling <input type="checkbox"/> Production <input checked="" type="checkbox"/> Disposal <input type="checkbox"/> Workover <input type="checkbox"/> Emergency <input type="checkbox"/> Lined <input type="checkbox"/> Unlined <input checked="" type="checkbox"/> Liner type: Synthetic <input type="checkbox"/> Thickness _____ mil Clay <input type="checkbox"/> Pit Volume <u>154 ±</u> bbl	Volume: _____ bbl Type of fluid: _____ Construction material: _____ Double-walled, with leak detection? Yes <input type="checkbox"/> If not, explain why not. _____
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet (20 points) 50 feet or more, but less than 100 feet (10 points) 0 100 feet or more (0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes (20 points) No (0 points) 0
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet (20 points) 200 feet or more, but less than 1000 feet (10 points) 10 1000 feet or more (0 points)
	Ranking Score (Total Points) 10

If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you are burying in place) onsite ☒ offsite ☐ If offsite, name of facility _____. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☒ Yes ☐ If yes, show depth below ground surface _____ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments:
24' x 12' x 3'± deep unlined production pit, center located at approximately 120 Feet South 17° West of wellhead.
Use backhoe to collect 6-point composite sample for lab testing.



I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐, or an (attached) alternative QCD-approved plan ☐.

Date: January 14, 2008

Printed Name/Title Jeffrey C Blagg, agent

Signature Jeffrey C. Blagg

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval: Deputy Oil & Gas Inspector,
District #3

Printed Name/Title _____

Signature B. L. Lell

Date: FEB 12 2008

30-013-26034

36.27905 x 101.89049

CLIENT: <u>DUGAN</u>	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	LOCATION NO: _____ COCR NO: <u>3693</u>
FIELD REPORT: PIT CLOSURE VERIFICATION		PAGE No: <u>1</u> of <u>1</u>
LOCATION: NAME <u>SILVER MEDAL</u> WELL #: <u>1</u> TYPE <u>PROD</u> QUAD/UNIT <u>M</u> SEC: <u>27</u> TWP: <u>24N</u> RNG: <u>10W</u> PM: <u>NM</u> CNTY: <u>SJ</u> ST: <u>NM</u> QTR/FOOTAGE: <u>620 FSL x 620 FWL</u> CONTRACTOR: <u>SIERRA</u>		DATE STARTED <u>12/6/07</u> DATE FINISHED <u>12/6/07</u> ENVIRONMENTAL SPECIALIST <u>JCB</u>
EXCAVATION APPROX. _____ FT. x _____ FT. x _____ FT. DEEP. CUBIC YARDAGE: _____ DISPOSAL FACILITY: _____ REMEDIATION METHOD: <u>CLOSE AS IS</u> LAND USE: <u>RANGE - BLM</u> LEASE: <u>NM 21741</u> FORMATION: <u>BISTI-GAL</u>		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY <u>120</u> FT. <u>S 17 W</u> FROM WELLHEAD DEPTH TO GROUNDWATER: <u>>100</u> NEAREST WATER SOURCE: <u>>1000</u> NEAREST SURFACE WATER <u>>200</u> NMOC D RANKING SCORE: <u>10</u> NMOC D TPH CLOSURE STD: <u>1000</u> PPM		
SOIL AND EXCAVATION DESCRIPTION:		OVM CALIB. READ. = <u>53.3</u> ppm OVM CALIB. GAS = <u>100</u> ppm RF = <u>0.52</u> TIME: <u>0900</u> am/pm DATE: <u>12/6</u>
SOIL TYPE: SAND / <u>SILTY SAND</u> / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER _____ SOIL COLOR: <u>TAN</u> COHESION (ALL OTHERS): NON COHESIVE / <u>SLIGHTLY COHESIVE</u> / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): LOOSE / <u>FIRM</u> / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE DRY / <u>SLIGHTLY MOIST</u> / MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED. <u>YES</u> / NO EXPLANATION - <u>3'-6' ON EAST SIDE ONLY</u> HC ODOR DETECTED: YES / NO EXPLANATION - _____ SAMPLE TYPE. GRAB / COMPOSITE - # OF PTS. _____ ADDITIONAL COMMENTS: <u>24 x 12 x 3 +/- USE BACKHOE TO DIG INTO PIT & SAMPLE.</u>		

FIELD 418.1 CALCULATIONS							
SAMP. TIME	SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)

SCALE

0 FT

PIT PERIMETER

**OVM
READING**

SAMPLE ID	FIELD HEADSPACE (ppm)
1 @	
2 @	
3 @	
4 @	
5 @	
6-Pt @ 6'	

PIT PROFILE

LAB SAMPLES

SAMPLE ID	ANALYSIS	TIME
6-pt	T/BTEX	0945

P.D = PIT DEPRESSION; B.G = BELOW GRADE, B = BELOW
 T H = TEST HOLE; ~ = APPROX.; T B = TANK BOTTOM

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / Dugan	Project #:	94034-010
Sample ID:	Silver Medal #1 Prod	Date Reported:	12-10-07
Laboratory Number:	43821	Date Sampled:	12-06-07
Chain of Custody No:	3693	Date Received:	12-10-07
Sample Matrix:	Soil	Date Extracted:	12-10-07
Preservative:	Cool	Date Analyzed:	12-10-07
Condition:	Cool & Intact	Analysis Requested:	8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	0.7	0.1
Total Petroleum Hydrocarbons	0.7	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: **Unlined Pit Closures.**


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / Dugan	Project #:	94034-010
Sample ID:	Silver Medal #1 Prod	Date Reported:	12-10-07
Laboratory Number:	43821	Date Sampled:	12-06-07
Chain of Custody:	3693	Date Received:	12-10-07
Sample Matrix:	Soil	Date Analyzed:	12-10-07
Preservative:	Cool	Date Extracted:	12-10-07
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	0.9
Toluene	6.5	1.0
Ethylbenzene	ND	1.0
p,m-Xylene	1.8	1.2
o-Xylene	2.2	0.9
Total BTEX	10.5	


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Unlined Pit Closures.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA Method 8015 Modified
Nonhalogenated Volatile Organics
Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	12-10-07 QA/QC	Date Reported:	12-10-07
Laboratory Number:	43818	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	12-10-07
Condition:	N/A	Analysis Requested:	TPH

	I-Cal Date	I-Cal RF	C-Cal RF	% Difference	Accept. Range
Gasoline Range C5 - C10	05-07-07	1.1685E+003	1.1690E+003	0.04%	0 - 15%
Diesel Range C10 - C28	05-07-07	1.0852E+003	1.0857E+003	0.04%	0 - 15%

Blank Conc. (mg/L - mg/Kg)	Concentration	Detection Limit
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2


Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Range
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%
Diesel Range C10 - C28	2.4	2.3	4.2%	0 - 30%


Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	Accept. Range
Gasoline Range C5 - C10	ND	250	250	100.0%	75 - 125%
Diesel Range C10 - C28	2.4	250	250	99.0%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: QA/QC for Samples 43818 - 43823.


Analyst


Review

Client:	N/A	Project #:	N/A
Sample ID:	12-10-BTEX QA/QC	Date Reported:	12-10-07
Laboratory Number:	43818	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	12-10-07
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF	C-Cal RF	%Diff	Blank Conc	Detect Limit
		Accept Range 0 - 15%			
Benzene	7.8549E+007	7.8707E+007	0.2%	ND	0.1
Toluene	7.5087E+007	7.5238E+007	0.2%	ND	0.1
Ethylbenzene	6.1009E+007	6.1131E+007	0.2%	ND	0.1
p,m-Xylene	1.1650E+008	1.1673E+008	0.2%	ND	0.1
o-Xylene	5.6466E+007	5.6579E+007	0.2%	ND	0.1


Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff	Accept Range	Detect Limit
Benzene	4.2	4.1	2.4%	0 - 30%	0.9
Toluene	9.8	9.6	2.0%	0 - 30%	1.0
Ethylbenzene	3.5	3.2	8.6%	0 - 30%	1.0
p,m-Xylene	14.0	13.9	0.7%	0 - 30%	1.2
o-Xylene	4.7	4.7	0.0%	0 - 30%	0.9


Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	4.2	50.0	54.0	99.6%	39 - 150
Toluene	9.8	50.0	59.7	99.8%	46 - 148
Ethylbenzene	3.5	50.0	53.0	99.1%	32 - 160
p,m-Xylene	14.0	100	112	98.2%	46 - 148
o-Xylene	4.7	50.0	54.4	99.5%	46 - 148

ND - Parameter not detected at the stated detection limit.

References. Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for Samples 37818 - 43823.


Analyst


Review