

District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W. Grand Avenue, Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S St. Francis Dr, Santa Fe, NM 87505

State of New Mexico  
Energy Minerals and Natural Resources

Form C-144  
June 1, 2004

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.  
For downstream facilities, submit to Santa Fe office

**Pit or Below-Grade Tank Registration or Closure**

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐

Type of action Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator XTO Energy Inc Telephone 505 333-3207 e-mail address kim\_champlin@xtoenergy.com  
Address #382 County Road 3100, Aztec, NM 87410  
Facility or well name PO Pipkin #6F API # 30-045-33446 U/L or Qtr/Qtr \_\_\_\_\_ Sec 18G T 27N R 10W  
County San Juan Latitude 36.57615 Longitude 107.93379 NAD 1927 ☐ 1983 ☒  
Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

| Pit                                                                                                                                                                                                                                                                                                                                                                                                           | Below-grade tank                                                                                                                                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type: Drilling <input checked="" type="checkbox"/> Production <input type="checkbox"/> Disposal <input type="checkbox"/><br>Workover <input type="checkbox"/> Emergency <input type="checkbox"/><br>Lined <input checked="" type="checkbox"/> Unlined <input type="checkbox"/><br>Liner type Synthetic <input type="checkbox"/> Thickness <u>12</u> mil Clay <input type="checkbox"/><br>Pit Volume _____ bbl | Volume _____ bbl Type of fluid: _____<br>Construction material _____<br>Double-walled, with leak detection? Yes <input type="checkbox"/> If not, explain why not _____<br><div style="text-align: right;">RCVD JAN 23 '08<br/>OIL CONS. DIV.<br/>DIST. 3</div> |
| Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water)                                                                                                                                                                                                                                                                                                 | Less than 50 feet (20 points)<br>50 feet or more, but less than 100 feet (10 points)<br>100 feet or more (0 points)                                                                                                                                            |
| Wellhead protection area (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources)                                                                                                                                                                                                                                                                       | Yes (20 points)<br>No (0 points)                                                                                                                                                                                                                               |
| Distance to surface water (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses)                                                                                                                                                                                                                                                                 | Less than 200 feet (20 points)<br>200 feet or more, but less than 1000 feet (10 points)<br>1000 feet or more (0 points)                                                                                                                                        |
| Ranking Score (Total Points) 0 Points                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                |

**If this is a pit closure:** (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location (check the onsite box if you are burying in place) onsite ☒ offsite ☐ If offsite, name of facility \_\_\_\_\_ (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered No ☒ Yes ☐ If yes, show depth below ground surface \_\_\_\_\_ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations

Additional Comments

The drilling reserve pit associated with the subject well was closed per NMOCD and BLM guidelines and in accordance with XTO's drilling pit closure plan.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐, or an (attached) alternative OCD-approved plan ☐.

Date 01/21/2008

Printed Name/Title Kim Champlin/Environmental Representative Signature Kim Champlin

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval Deputy Oil & Gas Inspector,  
District #3

Printed Name/Title \_\_\_\_\_


Signature Branch Pelt

Date

FEB 12 2008

XTO ENERGY INC.  
P O PIPKIN No. 6F, 2330 FNL 1740 FEL  
SECTION 18, T27N, R10W, N.M.P.M., SAN JUAN COUNTY, N.M.  
GROUND ELEVATION: 5940' DATE: APRIL 24, 2006

NAD 83  
LAT. = 36.57615° N  
LONG. = 107.93379° W  
NAD 27  
LAT. = 36°34'34.1" N  
LONG. = 107°55'59.4" W




RESERVE PIT DIKE: TO BE 8' ABOVE DEEP SIDE (OVERFLOW - 3' WIDE AND 1' ABOVE SHALLOW SIDE).  
BLOW PIT: OVERFLOW PIPE HALFWAY BETWEEN TOP AND BOTTOM AND TO EXTEND OVER PLASTIC LINER AND INTO BLOW PIT.

NOTE: DAGGETT ENTERPRISES, INC. IS NOT LIABLE FOR UNDERGROUND UTILITIES OR PIPELINES. NEW MEXICO ONE CALL TO BE NOTIFIED 48 HOURS PRIOR TO EXCAVATION OR CONSTRUCTION.


ELEV. A-A'

C/L




ELEV. B-B'

C/L



ELEV. C-C'

C/L



NOTE: CONTRACTOR SHOULD CALL ONE-CALL FOR LOCATION OF ANY MARKED OR UNMARKED BURIED PIPELINES OR CABLES ON WELL PAD AND OR ACCESS ROAD AT LEAST TWO (2) WORKING DAYS PRIOR TO CONSTRUCTION.

|                    |          |             |                                                                                                                                                                                   |
|--------------------|----------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REGION<br>RESTATED | DATE     | REVISION BY | Daggett Enterprises, Inc.<br>Surveying and Oil Field Services<br>P. O. Box 15068 • Farmington, NM 87401<br>Phone (505) 326-1772 • Fax (505) 326-6019<br>NEW MEXICO L.S. No. 14831 |
|                    | 05/12/06 | G.V.        |                                                                                                                                                                                   |
| DATE               | 05/27/06 | DATE        | 05/27/06                                                                                                                                                                          |
| DATE               | 05/27/06 | DATE        | 05/27/06                                                                                                                                                                          |

