1625 N French Dr , Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

For drilling and production facilities, submit to appropriate NMOCD District Office.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes X No Type of action Registration of a pit or below-grade tank Closure of a pit or below-grade tank X _Telephone ___505_333-3100 ____e-mail address __kim_champlin@xtoenergy com Operator XTO Energy Inc Address #382 County Road 3100, Aztec, NM 87410 API# 30-045-33037 Kutz Federal #15 Sec 18P _U/L or Qtr/Qtr _ Facility or well name T 28N R 10W __ Longitude 107.9302778 County San Juan Latitude 36.6577778 NAD: 1927 🗌 1983 🔲 **RCVD FEB 14'08** Surface Owner Federal X State Private Indian Below-grade tank OIL CONS. DIV. Type Drilling X Production Disposal D Volume ____bbl Type of fluid __ DIST. 3 Construction material Double-walled, with leak detection? Yes If not, explain why not Lined \(\square\) Unlined \(\square\) Liner type Synthetic Thickness 12 mil Clay Pit Volume Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water) 100 feet or more (0 points) Yes (20 points) Wellhead protection area (Less than 200 feet from a private domestic Nο (0 points) water source, or less than 1000 feet from all other water sources) Less than 200 feet (20 points) Distance to surface water (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) irrigation canals, ditches, and perennial and ephemeral watercourses) 1000 feet or more (0 points) Ranking Score (Total Points) 0 Points If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks (2) Indicate disposal location (check the onsite box if your are burying in place) onsite X offsite I If offsite, name of facility_ (3) Attach a general description of remedial action taken including remediation start date and end date (4) Groundwater encountered No 🔀 Yes 🔲 If yes, show depth below ground surface ft and attach sample results (5) Attach soil sample results and a diagram of sample locations and excavations The drilling reserve pit associated with the subject well was closed per NMOCD and BLM guidelines and in accordance with XTO's drilling pit closure plan I hereby certify that the information above is true and complete to the best of my knowledge and belief I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan . Date 02/12/2008 rim Champlin Printed Name/Title Kim Champlin/Environmental Representative Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. Deputy Oil & Gas Inspector, Approval FEB 2 6 2008 District #3 Printed Name/Title

XTO ENERGY INC. KUTZ FEDERAL No. 15, 990 FSL 660 FEL LAT: 36'39'28" N. SECTION 18, T28N, R10W, N.M.P.M., SAN JUAN COUNTY, N. M. GROUND ELEVATION: 5906, DATE: MARCH 1, 2004 LONG:107:55'49' NAD 27 CONSTRUCTION ZONE 8 F 4.7 (5) A c (6) F 5.6 G INSTALL DRAIN PIPE ON FRUITLAND FORMATIONS CALY F 0.1 2.1 Slopes Reserve Pil 똜 6' DEEP 10" DEEP BLOW PIT B' DEÉP 93, ાં (4) 701 F 0.9 15 LAYDOWN IN 1261381 W 35, Wellhead to Back RÉAR. Wellhead to Front-C -5.2 120 C. 0.0] 120 1 NEW ACCESS 275. (0 to 5%) 2 0 C' C 5.1 C 7.6 C 3.0 . ② A. 205' X 240' $(305' \times 340') = 2.38 \text{ ACRES}$ ġ, (3) RESERVE PIT DIKE: TO BE 8' ABOVE DEEP SIDE (OVERFLOW - 3' WIDE AND 1' ABOVE SHALLOW SIDE). BLOW PIT: OVERFLOW PIPE HALFWAY BETWEEN TOP AND BOTTOM AND TO EXTEND OVER PLASTIC LINER AND INTO BLOW PIT. DAGGETT ENTERPRISES, INC. IS NOT LIABLE FOR.
UNDERGROUND UTILITIES OR PIPELINES: NEW MEXICO
ONE CALL TO BE NOTIFIED 48 HOURS PRIOR TO
EXCAVATION OR CONSTRUCTION. NÖTE: ELEV. A-A 5920 5910 5900 5890. C/L ELEV. B-B 5920 5910 5900 Services I. Nu 87401 5) 326-6019 5890 Surveying and Oll Fleid Servi P. O. Box 15066 Framington, NU 8 Phon (56) 378-1772 - Fax (50) 28-HEW MEXICO L.S. No. 14627 C/L ELEV. C-C' 5920 5910 5900 5890

NOTE: CONTRACTOR: SHOULD, CALL ONE-CALL FOR: LOCATION: OF: ANY MARKED OR: UNMARKED; BURIED PIPELINES OR: CABLES ON: WELL PAD AND OR ACCESS ROAD AT LEAST TWO: (2), WORKING DAYS, PRIOR TO CONSTRUCTION: