This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **Oil Conservation Division**

## Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Cono	coPhillip	s Inc.			Leas	se Name	SAN	JUAN 28	8-7		Well No155
Location of Wel	l: Unit L	_etter	K	Sec _	22	Twp	027N	Rg	е	007W API	# 30-039-20430
	N	ame of Re	servoir or F	Pool		Typ of Pr				Method of Prod	Prod Medium
Upper Completion	PC				Gas				Flow		Casing
Lower Completion	DK				Gas				Artific	ial Lift	Tubing
				Pr	e-Flow	Shut-in F	Pressu	re Data			
Upper	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)
Completion	2/4/2008				84 hours					150.5	Yes
Lower	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)
Completion	2/4/2008				36 hours					233.4	Yes
Commenced a	t: 2	2/5/2008 1	2:33:00 PN	1	Fle	<b>ow Test</b> Zo		oducing (	Upper	or Lower): Lo	wer
Time		Lapsed Time			PRESSURE F				one		
(date/time	)	Since*		Upi	Upper zone		zone	Temperature		Remarks	
2/5/2008 12:34:0	4 PM		0		163.8	474	1.2			both zones SI	
2/6/2008 12:34:2	/6/2008 12:34:22 PM 24				166.7 48		3.1		both zones SI, tu		rned on DK
2/7/2008 12:34:4	2/7/2008 12:34:48 PM 48				169.5					turned on PC	
Production rate	during to	est									
Oil:	BPOD Based on:				_Bbls. InHrs.					Grav.	GOR ·
Gas		MCF	PD; Tes	t thru (Oı	rifice or I	Meter)					, ,
				ħ/II	id-Teet (	Shut-In E	Pressi	re Data			
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)

(Continue on reverse side)

RCVD FEB 29 '08 OIL CONS. DIV.

DIST. 3

## Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)					
Time	Lapsed Time	PRES		Prod Zone	D				
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks				
		,							
				,					
Production rate during	g test								
Dil:BPOI	D Based on:	Bbls. In	Hrs.	Gr	avGOR				
Gas	MCFPD; Test tl	hru (Orifice or M	eter)						
Remarks:					· ·				
Re-Test									
hereby certify that th	e information herein o	contained is true	and complete	to the best of m	y knowledge.				
Approved:	B 2 9 2008	20	Operat	tor: ConocoPh	illips Inc.				
	onservation Division		By:	Philana Thomp	· · · · · · · · · · · · · · · · · · ·				
L/ Villar			-						
By:			Title: _	iviuiti-Skilled O	perator				
Title: Deput	y Oil & Gas Insp	ector,	Date: _	Date: Thursday, February 28, 2008					

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- I A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3

above

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows, 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aziec District Office of the New Mexico Oii Conservation Division on Northwest New Mexico Parker Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)