Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROV	VED.
OMB No. 1004-	0137
Evniran Inly 21	201

5. Lease Serial No. SF 047039B

					01 0470000			
SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6 If Indian, Allottee or Tribe Name				
SUBMIT	IN TRIPLICATE - Oth	er-instructions on	page 2 C		7 If Unit of CA/Agre	ement, l	Name and/or No	
1 Type of Well								
Oıl Well	ell Other	MAR 0	3 2008		8. Well Name and No Birnson Federal 1	)		
2 Name of Operator Robert L. Bayless, Producer LLC		Bureau of Land	d Managemen	t	9. API Well No. 30-045-07530			
3a. Address		F	Field Office (include area code		10. Field and Pool or	Explora	tory Area	
PO Box 168 Farmington, NM 87499		505-326-2659		•	Basin Fruitland Coa	al	•	
4 Location of Well (Footage, Sec., T., 760' FNL and 1586' FWL (Unit C), Sec. 17, T. 28	R.,M., or Survey Descripti BN, R. 10W	ion)			11. Country or Parish San Juan County,	-	· · · · · · · · · · · · · · · · · · ·	
12. CHEC	K THE APPROPRIATE	BOX(ES) TO INDI	CATE NATURE	OF NOTIC	L CE, REPORT OR OTH	IER DA	TA	
TYPE OF SUBMISSION			TYP	E OF ACT	TON			
Notice of Intent	Acidize	☐ Deepe	en	☐ Prod	uction (Start/Resume)		Water Shut-Off	
✓ Notice of Intent	Alter Casing	_ :	ire Treat		amation		Well Integrity	
Subsequent Report	Casing Repair	☐ New (	Construction	Reco	mplete		Other	
	Change Plans	Plug a	and Abandon	Tem:	porarily Abandon			
Final Abandonment Notice	Convert to Injection	on Plug I	Back	Wate	er Disposal			
determined that the site is ready for Robert L. Bayless Producer LLC into between 465' and 480' below KB level cement with a minimum of 70 sacks sacks of cement will be present on pressure tested to 500 psi for 30 minus Steve Mason with the New Mexico Beauty Villanueva with the New Mexico Beauty V	ends to repair a casing rel. There is circulation (hole-casing annular v ocation to ensure suffic nutes to ensure integrit Bureau of Land Manage	through the casir olume) of Type V client cement is use y. ement verbally ap	ng leak between cement with 2% ed. There will be proved of this wo	the casing CaCl by 6 a 50' plu ork on Fric	g and the bradenhead circulating cement to g left in the casing. day, February 29, 20	id valve surface Upon di 08 at 7:	at surface. It is intended to the bradenhead. It is out, the casing will but am.	led to 300
						RCI	VD MAR 5 '08	
						OII	_ CONS. DIV.	
^	,						DIST. 3	
14 I hereby certify that the foregoing is t	rue and correct.							
Name (Printed/Typed) Catlain H. Richardson			Title Operation	s Engine	er			
Signature Catlain	Richard	lson	Date 02/29/200	08				
	THIS SPAC	E FOR FEDE	RAL OR STA	TE OF	FICE USE			
Approved by							•	
Original S	igned: Stephen Ma	son	Title			Date	MAR 0 4 2008	
Conditions of approval, if any, are attached that the applicant holds legal or equitable tentitle the applicant to conduct operations	itle to those rights in the su		ertify	Market		12416		

Title 18 U S.C Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,