

250-30-045-27104

2-30-045-09760

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit B Sec. 11 Twp 30 Rng 09

Name of Well/Wells. or Pipeline Serviced _____

Lindsey Com. #250, AND #2

Elevation 5882 Completion Date 6/30/94 Total Depth 390' Land Type F

Casing Strings, Sizes, Types & Depths 6/29 SET 99' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 21 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

USED 10 SACKS OF CEMENT, TO PLACE A 30' (85'-115') PLUG TO STOP GAS.

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT WATER AT 140', 180', AND 275'. WATER WAS

FRESH. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: 385'

Ground bed depth with type & amount of coke breeze used: 390' DEPTH.

USED 97 SACKS OF ASBURY 218R (4850#)

Depths anodes placed: 362', 354', 326', 318', 310', 302', 294', 286', 278', 232', 224', 196', 188', 180', 172'.

Depths vent pipes placed: SURFACE TO 390'.

Vent pipe perforations: BOTTOM 270'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.