

SA - 30-045-22490

9 - 30-045-21818

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit F Sec. 17 Twp 31 Rng 10

Name of Well/Wells. or Pipeline Serviced _____

Hudson #5A AND SCOTT #9

Elevation 5993 Completion Date 8/23/94 Total Depth 330' Land Type F

Casing Strings, Sizes, Types & Depths 8/21 Set 99' of 8" PVC Casing.

NO GAS OR WATER, BUT 38' (12'-40' + 60'-70') OF BOULDERS WERE ENCOUNTERED DURING CASING

If Casing Strings are cemented, show amounts & types used Cemented

WITH 18 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 150', AND MORE FRESH

WATER AT 305'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 330' DEPTH.

USED 76 SACKS OF ASBURY 218R (3800#)

Depths anodes placed: 300', 285', 260', 252', 244', 236', 228', 220', 212', 204', 196', 188', 180', 172' + 164'.

Depths vent pipes placed: SURFACE TO 330'.

Vent pipe perforations: BOTTOM 210'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.