

9- 30-039-07307
66- 30-039-07295

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 29 Twp 28 Rng 5

Name of Well/Wells or Pipeline Serviced SAN JUAN 28-5 UNIT #9, #66

cps 730w

Elevation 6571' Completion Date 4/25/66 Total Depth 280' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. N/A

RECEIVED
MAY 31 1991
OIL CO.

Depths gas encountered: N/A

Type & amount of coke breeze used: 5000 lbs.

Depths anodes placed: 255', 249', 210', 204', 198', 192', 143', 137'

Depths vent pipes placed: 255' OF 3/4" HOSE

Vent pipe perforations: 135' TO 165' & 195' TO 255'

Remarks: gb #1

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

4 3/4" Dia - #7 = 60'

Date 4-25-66

Well Name SULL 28-5 #9 & SULL 28-5 #66		CPS No. 730 W	
Location SW-29-28-5		Work Order No. 184-52634-50-20	
Anode Hole Depth 2.80	Total Drilling Rig Time 18 1/2	Type & Size Bit Used 246403 - 220'	
No. Sacks Lost Circulation Mat'l Used 1	Anode Depth	No. Sacks Mud Used 2	
		#1 255	#2 249
		#3 210	#4 204
		#5 198	#6 192
Total Lbs. Coke Used 5000	Anode Output (Volts)		
	#1 5.0	#2 4.5	#3 5.8
	#4 6.1	#5 5.7	#6 4.9
Total Circuit Resistance Volts 11.1	Amps 13.0	Ohms 0.85	
		No. Ft. Surface Cable Conduit 1888' on Anodes	
		7 143	8 137
		9 NO	
		7 4.7	8 4.3
		9 NO	

Drilling Log (Attach Hereto). ☐

Remarks: Static R_s's 600' E #9 = .70 600' E #66 = .68

3/4" Plastic Hose Tied to No. 1 Anode With Perforation
From 135 To 165 & From 195 To 255'
10 lbs Chemical

30-20-3 Neg. Rectifier Good All Ser. # 65C6676

All Construction Completed

(Signature)

GROUND BED LAYOUT SKETCH

823'
1888'
2711' TOTAL #8 WIRE



